

## Rolling TV Cart with Rechargeable Battery Power for 60" to 100" Displays

MODEL NUMBER: DMCS60100XXBB



Height-adjustable mobile cart with rechargeable battery system lets you move your flat-panel display smoothly from one room to another.

### Features

#### Move Your Flat-Panel Display or Interactive Whiteboard Wherever Your Audience Is

This rugged rolling TV stand combines a height-adjustable display mount with the convenience of a mobile cart. Mount your flat-panel television, digital whiteboard or touchscreen monitor to the all-metal unit, and then roll it safely and smoothly from room to room. The DMCS60100XXBB lets you deliver your message in corporate, education, healthcare, commercial, hospitality, retail, government and other settings requiring flexibility in a screen's location.

#### Comes Ready to Roll Wherever You Need to Go

A mobile stand with four-inch swivel casters allows you to roll the DMCS60100XXBB into any office, conference room, huddle space or classroom best suited for cost-efficient resource sharing. Ease of movement allows collaborative workflow to happen in any location and maximizes usage to increase engagement, creativity and productivity. Handles on the support columns help you guide the cart's movement. The casters lock into place to keep the stand securely in position while at rest.

#### No Need to Limit Your Presentations to Areas Where Wall Outlets Are Convenient

The DMCS60100XXBB is designed to encourage and assist group collaboration and audience participation. To support this goal, an enclosed, rechargeable lithium iron phosphate (LiFePO4) battery system powers the display for up to 90 minutes without being plugged into a wall outlet. This allows you to give your presentations in areas where no outlets are present or are too far away. LEDs monitor battery charge level in real time. Plug the system into a standard AC outlet to charge the battery when not in use.

#### Raise and Lower the Screen to Find the Most Comfortable Viewing Angle

The height-adjustable TV floor stand fits most flat-panel displays, whiteboards and monitors from 60 to 100 inches. Its steel frame withstands the stress of repeated adjustments and supports up to 220 pounds (99.8 kg). You can raise or lower the height of the display from 47 to 65 inches above the floor. You can also tilt the screen to achieve the most comfortable viewing angle.

#### Conveniently Place Peripherals and Manage Cables

A durable shelf holds audio/video and other components, such as laptops, projectors, webcams and Blu-ray players. Cables can be routed through the columns to keep them hidden and avoid excessive clutter.

#### VESA-Compliant Mounting Ensures Display Compatibility

### Highlights

- Ideal for rolling your flat-panel TV through offices, classrooms and conference rooms
- Rechargeable battery allows up to 90 min. of display use without plugging into outlet
- Durable steel frame blends into any room décor and supports up to 220 lb. (99.8 kg.)
- 4 in. swivel casters enable smooth rolling and lock to secure the cart at rest
- Built-in shelf accommodates laptops, projectors, webcams, Blu-ray players, etc.

### Applications

- Bring a digital whiteboard or interactive display into a conference room or classroom for a virtual meeting or brainstorming session
- Move a flat-panel display into a lobby, hallway or trade show booth to create temporary digital signage
- Show videos in a multipurpose area, such as a hotel lobby or lecture hall, where a permanent display is impractical
- Roll your television into a secure area for storage when not in use

### System Requirements

- Flat-screen television, monitor, digital whiteboard or interactive display from 60 to 100 in.
- Supports the following VESA patterns: 200 x 200, 200 x 300, 200 x 400, 200 x 500, 300 x 200, 300 x 300, 300 x 400, 300 x 500, 300 x 600, 400 x 200, 400 x 300, 400 x 400, 400 x 500, 400 x 600, 500 x 200, 500 x 300, 500 x 400, 500 x 500, 500 x 600, 600 x 300, 600 x 400, 600 x 500, 600 x 600, 600 x 900, 700 x 300, 700 x 400, 700 x 500, 700 x 600, 800 x 300, 800 x 400, 800 x 500, 800 x 600, 900 x 400, 900 x 500, 1000 x 400, 1000 x 500, 1000 x 600

### Package Includes

- Heavy-duty mobile floor stand
- Rechargeable lithium-ion battery

VESA (Video Electronics Standards Association) promotes uniformity in the video electronics industry by developing standards for TVs and monitors. For hassle-free display compatibility, this mount supports most VESA mounting hole patterns.

system

- HC350SNR power inverter/charger, 300W
- 32Ah Ultralife battery
- (4) Rolling casters, 4 in.
- Owner's manual

## Specifications

OVERVIEW	
UPC Code	037332260345
Product Type	Mobile TV cart with battery system
Device Compatibility	Monitor/HDTV
POWER	
Input Voltage(s)	120V
Power Cord Length (ft.)	6
Battery	<b>Battery Model Number:</b> Ultralife URB12350 <b>Mobile Power Source:</b> Lithium Iron Phosphate (LFP) Battery <b>Battery Capacity:</b> 32 Ah <b>Battery Voltage (VDC):</b> 12.8 <b>Battery Runtime:</b> 90 mins (typical, based on 240W load) <b>Battery Runtime Details:</b> 180W – 120min 200W – 100 min 240W – 90 min 300W – 75 min 420W – 55 min <b>Battery Recharge Time:</b> 2.8 hrs <b>Battery Cycle Life:</b> 1,500 cycles
Inverter/Charger	<b>Inverter Model Number:</b> HC350SNR <b>Output Voltage:</b> 120V <b>Pure Sine Wave Output:</b> Yes <b>Output Capacity:</b> 300W <b>Battery Recharge:</b> Internal ATS powers connected equipment and recharges battery simultaneously
PHYSICAL	
Color	Black; Silver
Material of Construction	Aluminum, Steel
Motion	Tilt
Mounting Location	Floor
Degrees of Motion	+5° to -10°
Minimum Screen Size (in.)	60
Maximum Screen Size (in.)	100
Maximum Weight Capacity (lbs.)	150
Maximum Weight Capacity (kg)	68
Number of Displays	1
Shipping Weight (kg)	57.15
Unit Dimensions (hwd / in.)	49.000 x 27.000 x 22.500

Unit Dimensions (hwd / cm)	124.5 x 70 x 57
Unit Weight (lbs.)	116
Unit Weight (kg)	52.62
Assembly Required	Yes
<b>FEATURES &amp; SPECIFICATIONS</b>	
Antimicrobial	No
Cord Management	Yes
Tools Necessary	No
Security Lock	No
Built-in Cable Management	No
Pre-Installed Casters	Yes
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	ANSI/AAMI ES60601-1; CAN/CSA-C22.2 No. 601.1; CAN/CSA-C22.2 No. 60601-1 (Canada); UL 1778; UL 60601-1
Product Compliance	RoHS; REACH
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	2-year limited warranty