## **Product data sheet**

Specifications





## Limit switch head, Limit switches XC Standard, ZCKD, thermoplastic roller lever

ZCKD15

Main	
Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Rotary head
Product compatibility	XCKL XCKM
Associated body	ZCKMD39 ZCKL1 ZCKLD31H7 ZCKLD35H7 ZCKMD35 ZCKM1H29 ZCKM5 ZCKM1H29 ZCKLD39H7 ZCKM8H29 ZCKL5 ZCKM1 ZCKM8H7 ZCKM8H7 ZCKM8H7 ZCKLD37H7 ZCKLD31 ZCKMB129 ZCKM8H29 ZCKM8H29 ZCKMB129 ZCKMB27 ZCKMD35H7 ZCKLD31 ZCKLD31 ZCKLD31 ZCKLD31 ZCKLD31 ZCKLD31 ZCKLD31 ZCKLD31 ZCKLSCKLB6 ZCKLSCKLSCKMB6 ZCKLSCKLSCKLSCKMB6 ZCKLSCKLSCKLSCKMB6 ZCKLSCKLSCKLSCKMB6 ZCKLSCKLSCKLSCKMB6 ZCKLSCKLSCKLSCKMB6 ZCKLSCKLSCKMB6 ZCKLSCKLSCKMB6 ZCKLSCKLSCKMB7 ZCKMB6 ZCKLSCKLSCKMB7 ZCKMB6 ZCKLSCKMB7 ZCKMB11 ZCKMB111 ZCKMB11 ZCKMB111 ZCKMB11 ZCKMB111 ZCKMB11 ZCKMB1 ZCKMB

ZCKLD37 ZCKMD39H29 ZCKL8H7 ZCKMD39H7 ZCKMD37H29 ZCKLD35

Movement of operating head	Rotary
	Roller lever spring return thermoplastic
Type of operator	
Type of approach	Lateral approach, 2 directions
Complementary	
Switch actuation	By 30° cam
Positive opening	With
Head material	Metal
Environment	
Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient air temperature for storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment
De aldo o 11. 21	
Packing Units Unit Type of Package 1	PCE
	1
Number of Units in Package 1	
Package 1 Height	1.34 in (3.400 cm)
Package 1 Width	2.44 in (6.200 cm)
Package 1 Length	3.07 in (7.800 cm)
Package 1 Weight	3.17 oz (90.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	28
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	5.91 in (15.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	6.17 lb(US) (2.800 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	896
Package 3 Height	30.31 in (77.000 cm)
Package 3 Width	31.50 in (80.000 cm)
Package 3 Length	23.62 in (60.000 cm)
Package 3 Weight	210.42 lb(US) (95.444 kg)
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

## **Contractual warranty**

Warranty

18 months

Recommended replacement(s)