

## Han Yellock 60HSM 1xM40 with bulkhead h.



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 11 12 600 1213  |
| Specification      | Han Yellock 60HSM 1xM40 with bulkhead h.  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/11126001213">https://b2b.harting.com/11126001213</a> |

### Identification

|                             |                                 |
|-----------------------------|---------------------------------|
| Category                    | Hoods/Housings                  |
| Series of hoods/housings    | Han-Yellock®                    |
| Type of hood/housing        | Surface mounted housing         |
| Description of hood/housing | incl. bulkhead mounted housings |

### Version

|                      |  |
|----------------------|--|
| Size                 | Han-Yellock® 60                            |
| Version              | Side entry                                 |
| Cable entry          | 1x M40                                     |
| Locking type         | Screw locking                              |
| Field of application | Hoods/housings for industrial applications |

### Technical characteristics

|  |  |
|--|--|
| Limiting temperature                   | -40 ... +125 °C                                |
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Un-/locking temperature                | -10 ... +85 °C                                 |
| Degree of protection acc. to IEC 60529 | IP65<br>IP67                                   |

### Material properties

|                         |                       |
|-------------------------|-----------------------|
| Material (hood/housing) | Aluminium die-cast    |
| Surface (hood/housing)  | Powder-coated         |
| Colour (hood/housing)   | RAL 7021 (black grey) |



**Pushing Performance**  
Since 1945

## Material properties

|   |                |
|---|----------------|
| Material (seal)                           | NBR            |
| Material flammability class acc. to UL 94 | V-0            |
| RoHS                                      | compliant      |
| ELV status                                | compliant      |
| China RoHS                                | e              |
| REACH Annex XVII substances               | Not contained  |
| REACH ANNEX XIV substances                | Not contained  |
| REACH SVHC substances                     | Not contained  |
| California Proposition 65 substances      | Yes            |
| California Proposition 65 substances      | Lead<br>Nickel |

## Specifications and approvals

|                |                          |
|----------------|--------------------------|
| Specifications | IEC 60664-1<br>IEC 61984 |
| CE             | Yes                      |
| Approvals      | DNV GL                   |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Net weight                     | 610 g                                    |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140110298                            |
| eCl@ss                         | 27440202 Shell for industrial connectors |