


SOT23 NPN SILICON PLANAR MEDIUM POWER TRANSISTOR

BCX19

ISSUE 4 – MARCH 2001

PARTMARKING DETAILS – BCX19 - U1
BCX19R - U4

COMPLEMENTARY TYPES - BCX17



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Emitter Voltage	V_{CES}	50	V
Collector-Emitter Voltage	V_{CEO}	45	V
Emitter-Base Voltage	V_{EBO}	5	V
Peak Pulse Current	I_{CM}	1000	mA
Continuous Collector Current	I_C	500	mA
Base Current	I_B	100	mA
Peak Base Current	I_{BM}	200	mA
Power Dissipation at $T_{amb}=25^\circ\text{C}$	P_{TOT}	330	mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Cut-Off Current	I_{CBO}			100 200	nA μA	$V_{CB}=20\text{V}$ $V_{CB}=20\text{V}, T_j=150^\circ\text{C}$
Emitter-Base Cut-Off Current	I_{EBO}			10	μA	$V_{EB}=5\text{V}$
Base-Emitter Voltage	V_{BE}			1.2	V	$I_C=500\text{mA}, V_{CE}=1\text{V}^*$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$			620	mV	$I_C=500\text{mA}, I_B=50\text{mA}^*$
Static Forward Current Transfer Ratio	h_{FE}	100 70 40		600		$I_C=100\text{mA}, V_{CE}=1\text{V}$ $I_C=300\text{mA}, V_{CE}=1\text{V}^*$ $I_C=500\text{mA}, V_{CE}=1\text{V}^*$
Transition Frequency	f_T		200		MHz	$I_C=10\text{mA}, V_{CE}=5\text{V}$ $f=35\text{MHz}$
Output Capacitance	C_{obo}		5.0		pF	$V_{CB}=10\text{V}, f=1\text{MHz}$

*Measured under pulsed conditions.