

## Touch panel - TP 10T/M 211 - 2701843

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 26.4 cm/10.4" TFT-Display (Analog resistive (polyester)), 640 x 480 Pixel (VGA), 65536 colors, Xscale<sup>®</sup> PXA320, 806 MHz, 2x USB host 1.1, 1x CompactFlash<sup>®</sup>, 1 x Ethernet (10/100 Mbps), RJ45, Windows CE 6.0 and User software: Visu+ / AX OPC Server. (Bus system: without)

### Why buy this product

- Short startup time
- Easy installation, low installation depth, and compact design
- Display available in sizes from 8.9 cm (3.8") to 38.1 cm (15")
- Visu+ RT and AX OPC server integrated as standard in all devices
- Energy efficient due to LED backlighting

### Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	3,200.000 g
Custom tariff number	84714100
Country of origin	Germany

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### Dimensions

External dimension, width	328 mm
External dimension, height	265 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	303 mm
Installation dimension, height	238 mm
Installation dimension, depth	57 mm

#### Display

Display	26.4 cm/10.4" TFT
---------	-------------------

# Touch panel - TP 10T/M 211 - 2701843

## Technical data

### Display

Screen resolution	640 x 480 Pixel(s) (VGA)
Backlighting	LED
Display backlight MTBF	50000 h
Touch technology	Analog resistive (polyester)
Colors	65536 colors

### Computer data

Processor	Xscale® PXA320, 806 MHz
Operating systems	Windows® CE 6.0
User software	Visu+
	AX OPC Server
RAM	128 MB SDRAM
Mass storage	1 GB Flash
Network	1 x Ethernet (10/100 Mbps), RJ45
Interfaces	2x USB host 1.1
	1x CompactFlash®
Bus system	without

### General

Mounting type	Front installation
---------------	--------------------

### Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
	NEMA 4X
Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

### Device supply

Power supply unit	24 V DC ±20 %
-------------------	---------------

### Standards and Regulations

Shock	DIN EN 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

# Touch panel - TP 10T/M 211 - 2701843

## Classifications

### eCl@ss

eCl@ss 5.1	27242302
eCl@ss 6.0	27242302
eCl@ss 8.0	27242302
eCl@ss 9.0	27330201

### ETIM

ETIM 4.0	EC001412
ETIM 5.0	EC001412

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

## Approvals

### Approvals

---

#### Approvals

DNV / LR / ABS / RINA / GL / GL-SW / PRS / UL Listed / cUL Listed / GL

---

#### Ex Approvals

---

### Approval details

DNV <a href="http://exchange.dnv.com/tari/ A-13918">http://exchange.dnv.com/tari/ A-13918</a>
LR <a href="http://www.lr.org/en 14/20017">http://www.lr.org/en 14/20017</a>
ABS <a href="http://www.eagle.org/eagleExternalPortalWEB/ 14-HG1287593-PDA">http://www.eagle.org/eagleExternalPortalWEB/ 14-HG1287593-PDA</a>
RINA <a href="http://www.rina.org/en/index.aspx ELE086614XG">http://www.rina.org/en/index.aspx ELE086614XG</a>
GL <a href="http://www.gl-group.com/newbuilding/approvals/index.html 54463-07 HH">http://www.gl-group.com/newbuilding/approvals/index.html 54463-07 HH</a>

# Touch panel - TP 10T/M 211 - 2701843

## Approvals

GL-SW 54463-07 HH

PRS <http://www.prs.pl/TE/2110/880590/16>

UL Listed <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 205795

cUL Listed <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 205795

GL  <http://www.gl-group.com/newbuilding/approvals/index.html>

## Accessories

### Accessories

#### Battery module

Battery / accumulator - HMI BATTERY - 2701383

Lithium battery



---

## Mounting material

Mounting material - HMI WALL MOUNTING KIT - 2701380

HMI mounting kit for panel installation. The mounting kit includes 2 spring clips.



Mounting material - HMI SCB MOUNTING KIT 4 - 2701384



HMI mounting kit for installation on a front plate. The mounting kit includes 4 x mounting brackets, 4 x screw threads, and a hexagonal wrench.

## Touch panel - TP 10T/M 211 - 2701843

### Accessories

---

#### Mounting material - HMI SCB MOUNTING KIT 6 - 2701385



HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, 6 x screw threads, and a hexagonal wrench.

---

#### Mounting material - HMI SCB MOUNTING KIT 8 - 2701387



HMI mounting kit for installation on a front plate. The mounting kit includes 8 x mounting brackets, 8 x screw threads, and a hexagonal wrench.

---

### Operating stylus

#### Touch pen - TOUCH PEN - 2701379



Touch pen for HMIs, silver coated. Delivery includes self-adhesive pen holder.

---

### Parameterization memory

#### Memory - CF FLASH 256MB - 2988780



Program and configuration memory, plug-in, 256 MB

---

### PCB plug

## Touch panel - TP 10T/M 211 - 2701843

### Accessories

Printed-circuit board connector - MSTB 2,5/ 3-STF - 1786844

Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 3, Pitch: 5 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Tin



---

### Protective foil

Protective foil - 10,4" DISPLAY PROTECTIVE FOIL - 2701376

Protective film set comprising 10 pieces of film for a 10.4" display. Including a squeegee to apply film and instructions.



---

### Storage medium

USB memory stick - USB FLASH DRIVE - 2402809



USB memory stick, 8 GB

---

Memory card - VL 1 GB CF - 2913155



CompactFlash® card, pluggable, 1 GB

---

Memory card - VL 4 GB CF - 2913157



CompactFlash® card, pluggable, 4 GB

## Touch panel - TP 10T/M 211 - 2701843

### Accessories

---

Memory card - VL 8 GB CF - 2913158



CompactFlash® card, pluggable, 8 GB

---