

## Relay connectors - ST-REL4-HG 60/21-21 - 2823418

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Relay connector, equipped with Hengstler miniature round relay, contacts (AgCdO+Au): small to large loads, 2 PDT, input voltage 60 V DC, with light indicator, can be plugged on basic termination blocks

The illustration shows version ST-REL 4-HG 24/21-21



### Key commercial data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 pc  |
| GTIN                                 | <br>4 017918 077389 |
| Weight per Piece (excluding packing) | 69.4 GRM  |
| Custom tariff number                 | 85364190  |
| Country of origin                    | Germany   |

### Technical data

#### Dimensions

|        |         |
|--------|---------|
| Width  | 27 mm   |
| Height | 33 mm   |
| Depth  | 66.5 mm |

#### Ambient conditions

|   |                  |
|---|------------------|
| Ambient temperature (operation)         | -20 °C ... 60 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

#### Coil side

|   |                 |
|---|-----------------|
| Nominal input voltage $U_N$               | 60 V DC         |
| Input voltage range in reference to $U_N$ | 0.8 ... 1.1     |
| Typical input current at $U_N$            | 17 mA           |
| Typical response time                     | 15 ms (with DC) |

## Relay connectors - ST-REL4-HG 60/21-21 - 2823418

### Technical data

#### Coil side

|                           |   |
|---------------------------|---|
| Typical release time      | 25 ms (with DC)   |
| Operating voltage display | Yes   |
| Protective circuit        | Damping diode, polarity protection Damping diode, polarity protection diode |

#### Contact side

|                                       |                         |
|---------------------------------------|-------------------------|
| Contact type                          | Single contact, 2-PDT   |
| Contact material                      | AgCdO, hard gold-plated |
| Maximum switching voltage             | 250 V AC/DC             |
| Maximum inrush current                | 6 A                     |
| Limiting continuous current           | 6 A                     |
| Interrupting rating (ohmic load) max. | 120 W (at 24 V DC)      |
|                                       | 180 W (at 48 V DC)      |
|                                       | 105 W (at 60 V DC)      |
|                                       | 60 W (at 110 V DC)      |
|                                       | 90 W (at 220 V DC)      |
|                                       | 1250 VA (for 250 V AC)  |

#### General

|  |                                   |
|--|-----------------------------------|
| Test voltage relay winding/relay contact | 2 kV AC (50 Hz, 1 min.)           |
| Test voltage PDT/PDT                     | 2.5 kV AC (50 Hz, 1 min.)         |
| Operating mode                           | 100% operating factor             |
| Mechanical service life                  | Approx. 10 <sup>7</sup> cycles    |
| Standards/regulations                    | DIN VDE 0110b, Gr. C for 250 V DC |
|  | DIN VDE 0160 (in relevant parts)  |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27371104 |
| eCl@ss 4.1 | 27371104 |
| eCl@ss 5.0 | 27371001 |
| eCl@ss 5.1 | 27371001 |
| eCl@ss 6.0 | 27371001 |
| eCl@ss 7.0 | 27371001 |
| eCl@ss 8.0 | 27371001 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000196 |
|----------|----------|

# Relay connectors - ST-REL4-HG 60/21-21 - 2823418

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000196 |
| ETIM 4.0 | EC000196 |
| ETIM 5.0 | EC000196 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211916 |
| UNSPSC 7.0901 | 39121515 |
| UNSPSC 11     | 39121515 |
| UNSPSC 12.01  | 39121515 |
| UNSPSC 13.2   | 39121515 |

## Approvals

### Approvals

---

Approvals

GOST / GOST

---

Ex Approvals

---

Approvals submitted

---

### Approval details



## Drawings

# Relay connectors - ST-REL4-HG 60/21-21 - 2823418

Circuit diagram

