Product data sheet

Specifications



Glazed door with locking for 2 locks PLM3025 (former version)

NSYDPLM3025TG

|--|

Range	Thalassa
Accessory / separate part category	Enclosure accessory
Product or component type	Door
Application	Multi-purpose
For enclosure nominal dimensions	-
Mounting location	Front
Range compatibility	Thalassa (Thalassa PLM)
Device composition	1 door
Quantity per set	Set of 1

Complementary

Material	Door: polyester reinforced with fibreglass
Colour	Door: grey (RAL 7035)
Door type	Glazed
Door opening side	Right (120 °) Left
Maximum load	50 kg/m²
Height	308 mm
Width	255 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.0 cm
Package 1 Width	2.0 cm
Package 1 Length	30.0 cm
Package 1 Weight	563.0 g

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

Recommended replacement(s)