



General Information

| | |
|---------------|--|
| Series | JSP |
| Dielectric | Metallized Polyester Stacked |
| Style | Radial |
| Features | DC Multipurpose Applications |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Miscellaneous | This Part Number Has One Or More Features That Make It Nonstandard, Semi-Standard, Or Unusual Even Though It May Be A Catalog Part Number. Such Part Numbers Are Often Subject To Long Lead Times. Please Contact KEMET For Details. maxKO = 1890. |

Specifications

| | |
|-----------------------|-------------------------|
| Capacitance | 220 uF |
| Capacitance Tolerance | 10% |
| Voltage AC | 40 VAC |
| Voltage DC | 63 VDC, 35.4 VDC (125C) |
| Temperature Range | -55/+125°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 1% 1kHz |
| Insulation Resistance | 5.7 MOhms |
| Max dV/dt | 15 V/us |
| Inductance | 22 nH |

Dimensions

| | |
|----|-----------------|
| L | 41.5mm +0.3mm |
| H | 40mm +0.1mm |
| T | 20mm +0.3mm |
| S | 37.5mm +/-0.4mm |
| LL | 4mm +2mm |
| F | 1mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 126 |