


PA Supercapacitors

Cylindrical pack



Features

- 5.0 Volts
- Ultra-low ESR
- High capacitance
- Long cycle life
- Low leakage currents

Features

- Pulse power
- Bridge or hold-up power

Description

Eaton PowerStor supercapacitors are unique, ultra-high capacitance devices utilizing electrochemical double layer capacitor (EDLC) construction combined with new, high performance materials. This combination of advanced technologies allows Eaton to offer a wide variety of capacitor solutions tailored to specific applications that range from a few micro-amps for several days to several amps for milliseconds.



Powering Business Worldwide

Ratings

| | |
|-----------------------------|-----------------------|
| Capacitance | 0.22 F to 0.47 F |
| Maximum working voltage | 5.0 V |
| Surge voltage | 6.0 V |
| Capacitance tolerance | -20% to +80% (+20 °C) |
| Operating temperature range | - 25 °C to +70 °C |

Specifications

| Capacitance (F) | Vertical Part Number | Horizontal Part Number | Nominal ESR (Ω) (Equivalent Series Resistance) Measured @ 1 kHz | Nominal Dimensions (mm) | Typical Mass (grams/piece) |
|-----------------|----------------------|------------------------|--|-------------------------|----------------------------|
| 0.22 | PA-5ROV224-R | PA-5ROH224-R | 0.30 | 8.5 x 16.8 x 21.5 | 3.5 |
| 0.47 | PA-5ROV474-R | PA-5ROH474-R | 0.20 | 10.5 x 20.8 x 22.5 | 5.4 |


Performance

| Parameter | Capacitance change (% of initial value) | ESR (% of max. initial value) |
|--|---|-------------------------------|
| Life (1000 hours @ 70 °C @ 2.5 Vdc) | $\leq 30\%$ | $\leq 300\%$ |
| Storage - Low and High Temperature (1000 hours @ -25 °C and 85 °C) | $\leq 30\%$ | $\leq 300\%$ |


Dimensions (mm)

| Vertical Part Number | Horizontal Part Number | A | B | C | d' | D | D' | E | E' | F | P |
|----------------------|------------------------|----------------|------|------|------------------------------|----------------|----|----|-----------------------------|-----|------|
| PA-5ROV224-R | PA-5ROH224-R | 9.0 | 17.3 | 22.0 | 0.5 | 20 | 15 | 25 | 20 | 2.0 | 11.8 |
| PA-5ROV474-R | PA-5ROH474-R | 11.0 | 21.3 | 23.0 | 0.6 | 20 | 15 | 25 | 20 | 2.0 | 5.3 |
| Tolerances | | Maximum | | | ± 0.02 | Minimum | | | ± 0.5 | | |

Note: Longer lead is positive.



Vertical



Horizontal

Part numbering system

| P | A | — | 5 | R | 0 | V | 47 | 4 | -R |
|-------------|-----------------|---|-------------------------|--------------------------------|-----------------------------------|------------|------------------|---|----|
| Family Code | Version | | Voltage (V) R = Decimal | Configuration | Capacitance (μ F) | | | | |
| P Family | A=Ultra-Low ESR | | 5R0 = 5.0 V | V = Vertical H = Horizontal | Value | Multiplier | Standard product | | |
| | | | | | Example: 474 = 47 x 474 or 0.47 F | | | | |


Packaging information

- Standard packaging: Bulk, 100 units per bag
- Larger bulk packages available on request

Part marking

- Manufacturer
- Capacitance (F)
- Max Operating Voltage (V)
- Family Code (or part number)
- Polarity

Wave solder profile



| Profile Feature | Standard SnPb Solder | Lead (Pb) Free Solder |
|-------------------------------------|---|--|
| Preheat and soak | <ul style="list-style-type: none"> • Temperature max. (T_{smax}) • Time max. | <ul style="list-style-type: none"> 100 °C 60 seconds |
| Δ preheat to max Temperature | 160 °C max. | 160 °C max. |
| Peak temperature (T_p)* | 220 °C – 260 °C | 250 °C – 260 °C |
| Time at peak temperature (t_p) | 10 seconds max 5 seconds max each wave | 10 seconds max 5 seconds max each wave |
| Ramp-down rate | ~ 2 K/s min ~3.5 K/s typ ~5 K/s max | ~ 2 K/s min ~3.5 K/s typ ~5 K/s max |
| Time 25 °C to 25 °C | 4 minutes | 4 minutes |

Manual solder

+350 °C, 4-5 seconds. (by soldering iron), generally manual, hand soldering is not recommended.

Reflow soldering

Do not use reflow soldering using infrared or convection oven heating methods.

Cleaning/Washing

Avoid cleaning of circuit boards, however if the circuit board must be cleaned use static or ultrasonic immersion in a standard circuit board cleaning fluid for no more than 5 minutes and a maximum temperature of +60 °C. Afterwards thoroughly rinse and dry the circuit boards. In general, treat supercapacitors in the same manner you would an aluminum electrolytic capacitor.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
www.eaton.com/electronics

© 2015 Eaton
All Rights Reserved
Printed in USA
Publication No. 4392
October 2016

Eaton is a registered trademark.
All other trademarks are property of their respective owners.