

Han B Hood Coupler LC 2 Levers PG 29



| Part number | 09 30 024 1731 |
|--------------------|--------------------------------------|
| Specification | Han B Hood Coupler LC 2 Levers PG 29 |
| HARTING eCatalogue | https://b2b.harting.com/09300241731 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Hoods/Housings |
|--------------------------|------------------------|
| Series of hoods/housings | Han [®] B |
| Type of hood/housing | Cable to cable housing |
| Туре | Low construction |

Version

| Size | 24 B |
|----------------------------|---|
| Version | Top entry |
| Cable entry | 1x Pg 29 |
| Locking type | Double locking lever |
| Han-Easy Lock [®] | Yes |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|--|
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|-------------------------|--------------------|
| | |



Material properties

| Surface (hood/housing) | Powder-coated |
|--|--|
| Colour (hood/housing) | RAL 7037 (dust grey) |
| Material (seal) | NBR |
| Material (locking) | Polycarbonate (PC) Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate |
| ECHA SCIP number | 16ca3004-52e6-46fa-bf13-9c1e1b30f813 |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel Naphthalene |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |

Specifications and approvals

| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
|-----------|--|
| CE | Yes |
| Approvals | DNV GL |

Commercial data

| Packaging size | 1 |
|--------------------------------|---------------|
| Net weight | 230 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140047808 |

Product data sheet 09 30 024 1731 Han B Hood Coupler LC 2 Levers PG 29



Commercial data

eCl@ss

27440202 Shell for industrial connectors