

## TJM220605

<b>Series</b>	Series 1
<b>Type</b>	Feedthru
<b>Number of Contacts</b>	10
<b>Number of Contacts per Size</b>	10
<b>Contact Size</b>	20
<b>Contact Type</b>	Pin
<b>Contact Part Number</b>	M39029/1-101
<b>QPL</b>	M81714/7-DC1
<b>Mil-Spec</b>	Active Mil-Spec
<b>Temperature (C°)</b>	-65 to 200
<b>Insulation Resistance</b>	5000 Megahms at 25 degrees Celcius
<b>Dielectric Withstanding Voltage</b>	1500 VRMS at Sea Level 200 VRMS at 100,000 Ft.
<b>Amperage</b>	7.5 Amps
<b>Vibration and Shock</b>	MIL-T-81714 Paragraph 3.5 5 and 3 5.8
<b>Body</b>	Polyetherimide per ASTM-D5205
<b>Grommet</b>	Silicone Blend Elastomer per A-A-59588
<b>Contact Retainers</b>	Stainless Steel
<b>Socket/Pin Contacts</b>	Copper Alloy, Hard Gold Plated in Accordance with MIL-G-45204
<b>With or Without</b>	Without
<b>Color</b>	Blue
<b>Electronic Component Type</b>	N/A
<b>Electronic Component Part No.</b>	N/A
<b>Electronic Req. Qty</b>	N/A
<b>Engineering PDF</b>	Contact factory for drawing.
<b>Dimension Image</b>	
<b>Bussing or Circuit Configuration</b>	Contact factory for drawing.