



3 Type

A Mounting with countersunk screw

Metric table

Dimensions in: millimeters - inches

1 r	2 d ₁ Thread	b	d ₂	d ₃	l ₁	l ₂	l ₃	l ₄	Max. load F
45 <i>1.77</i>	M 6	13 <i>0.51</i>	19 <i>0.75</i>	9 <i>0.35</i>	12 <i>0.47</i>	13 <i>0.51</i>	8.5 <i>0.33</i>	0.5 <i>0.02</i>	500 N <i>112 lbf</i>
65 <i>2.56</i>	M 8	18 <i>0.71</i>	25 <i>0.98</i>	14 <i>0.55</i>	14 <i>0.55</i>	16 <i>0.63</i>	10.5 <i>0.41</i>	0.6 <i>0.02</i>	1000 N <i>225 lbf</i>

Specification

- Lever arm
Zinc die-cast
Powder coated
Black, RAL 9005, textured finish **● SW**
Silver, RAL 9006, textured finish **● SR**
- Latch housing
Stainless steel
- Countersunk screw
DIN 7991
Stainless steel (A2)
- RoHS compliant

Information

GN 720 stop latches may be used as stops, and feature a high degree of stability. The internal ball spring latch housing has four latching positions at a distance of 90° each. Thanks to the bolt attachment using the countersunk screw, the latching position can be easily selected. The latch arm is solid and may be machined, if required. The countersunk screw is enclosed as part of the set.

How to order	
1	Length r
2	Handle diameter d ₁
3	Type
4	Color

GN 720-65-M8-A-SW

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9
3.10