

**CRYSTAL CLOCK OSCILLATORS (SMD • Ceramic Package)**

RoHS compliant

**CSX-750F SERIES**


2000pcs/reel




**FEATURES**

- Available to supply voltage 5.0V or 3.3V.
- Low current consumption with output enable function (OE) or stand by function (STAND-BY).
- Suitable for various applications such as communication devices, AV devices and measuring instruments.

**DIMENSION [mm]**



**SOLDER PAD LAYOUT [mm]**



**STANDARD SPECIFICATIONS** \* Model is determined by the selection for the output enable or stand-by function, the frequency stability and the supply voltage.

Item	Model	CSX-750 FC (*)		CSX-750 FB (*)	CSX-750 FJ (*)
	OE				
	STAND-BY				
Frequency Range		1.8432MHz~39.999MHz	40.000MHz~75.000MHz	1.8432MHz~39.999MHz	40.000MHz~80.000MHz
Supply Voltage		Vdd : 5.0V±0.5V		Vdd : 3.3V±0.3V	
Frequency Stability	(*)	B : ±50ppm, C : ±100ppm, E : ±50ppm (-40°C~+85°C), F : ±100ppm (-40°C~+85°C)			
Operating Temperature Range		-20°C~+70°C (-40°C~+85°C)			
Storage Temperature Range		-55°C~+125°C			
Current consumption		25mA Max.	45mA Max.	15mA Max.	25mA Max.
Duty	TTL level (1.4V)	40~60%		—	
	CMOS level (1/2 Vdd)			45~55%	
Output Voltage	V <sub>OH</sub>	0.9Vdd Min.			
	V <sub>OL</sub>	0.4V Max.		0.1Vdd Max.	
Output Load	TTL	10TTL Max.		—	
	CMOS	50pF Max.		30pF Max.	30pF Max.
Rise and Fall Time		8 nsec Max.	6 nsec Max.	8 nsec Max.	6 nsec Max.
Start-up time		4 msec Max.	10 msec Max.	4 msec Max.	10 msec Max.
Input Voltage	V <sub>IH</sub>	2.0V Min.			
	V <sub>IL</sub>	0.8 V Max.		0.4V Max.	0.3Vdd Max.
Disable current		10mA Max.	20mA Max.	5mA Max.	—
Stand-by current		—		10 μA Max.	