

# XVS14BMW

Harmony XVS, Multi-sound siren, pre-wired, white colour, 0...105 dB, 43 tones, 12/24V DC



## Main

Range of Product	Harmony XVS
Product or Component Type	Multisound siren
Device short name	XVS

## Complementary

Color	White
Material	ASA (Acrylonitrile Styrene Acrylate) front ASA (Acrylonitrile Styrene Acrylate) back PC (polycarbonate) back cover
Net Weight	2.20 lb(US) (1 kg)
Marking	CE
Mounting Support	Bracket
Fixing Mode	3 holes Ø 9 mm
[Uimp] rated impulse withstand voltage	0.8 kV
Current consumption	350 mA 24 V 250 mA 12 V
Electrical connection	Cable 0.26...0.33 in (6.5...8.5 mm), 0.00 in <sup>2</sup> (0.33 mm <sup>2</sup> ) / AWG 22 signalling circuit) Cable 0.26...0.33 in (6.5...8.5 mm), 0.00 in <sup>2</sup> (0.52 mm <sup>2</sup> ) / AWG 20 power circuit)
Width	5.51 in (140 mm)
Height	4.49 in (114 mm)
Depth	8.78 in (223 mm)

## Environment

Signalling type	43 tones siren
Standards	EN 61000-6-2 EN 55014-2 EN 55022 EN 61000-6-3
Product Certifications	UL
Protective treatment	TC
Ambient Air Temperature for Storage	-31...158 °F (-35...70 °C)
Ambient air temperature for operation	14...122 °F (-10...50 °C)
Overvoltage category	Class II EN/IEC 61140
IP degree of protection	IP53 conforming to EN/IEC 60529
[Us] rated supply voltage	12 V DC 24 V DC
Noise level	0...105 dB continuous or intermittent tone)1 m

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

Category	22617 - XVC TOWER LIGHTS
Discount Schedule	XV
GTIN	3606480032943
Nbr. of units in pkg.	1
Package weight(Lbs)	3.02 lb(US) (1.37 kg)
Returnability	Yes
Country of origin	ID

## Packing Units

Package 1 Height	3.000 dm
Package 1 width	1.800 dm
Package 1 Length	1.850 dm

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------

## Siren

### Dimensions

mm  
in.

