

**Mechanical characteristics**  
cables

interface dimensions acc. to assembly code  
center conductor  
outer conductor  
mating life

**Components**

center conductor  
outer conductor  
other metal parts  
insulator

**Electrical characteristics**

impedance  
frequency  
return loss  
intermodulation  
voltage proof  
insulation resistance  
contact resistance  
center contact  
outer contact

**Environmental**  
operating temp.  
RoHS compliant

**Mechanische Eigenschaften**  
Kabel

Steckgesicht nach Montageanleitung  
Innenleiter  
Außenleiter  
Steckzyklen

**Bauteile**

Innenleiter  
Außenleiter  
sonstige Metallteile  
Isolierung

**Elektrische Eigenschaften**

Wellenwiderstand  
Frequenz  
Rückflussdämpfung  
Intermodulation  
Prüfspannung  
Isolationswiderstand  
Durchgangswiderstand  
Innenkontakt  
Außenkontakt

**Umgebung**

Betriebstemperatur  
RoHS konform

G 9: EZ 250 Suhner, Flexiform 401 Habia, RG-401/U, Sucoform 250 Suhner, UT-250 Micro-Coax

IEC 61169-54  
E06  
solder / löt  
solder / löt  
>100

**Materials / Material**

copper alloy / Kupferleg.  
brass / Messing  
brass / Messing  
PTFE

**Finish / Oberfläche**



Cu2Ag5  
Cu2Ag3  
Cu2Ag3


50 Ω  
0-6 GHz  
typ.: 1 GHz-40 dB; 2 GHz-34 dB; 4 GHz-28 dB  
< - 165 dBc 2x20 Watt  
2 kV<sub>eff</sub> / 50 Hz  
≥ 5 GΩ

≤ 1 mΩ  
≤ 1 mΩ

-55°C / +90°C  
2011/65/EU

ⓑ

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]
			gez./ drawn	26.05.2014	MA	
			gepr./ appr	05.06.2014	VM	co./approx. 44 g
Maßstab/ scale <b>2:1</b>				Benennung/ title <b>4.3-10 Panel Jack</b> <b>4.3-10 Kabeleinbaubuchse</b>		
untol. Maße/ dim. without tolerances according to				Untert./ doc. type <b>K</b>		Zeichnungsnr./ drawing no. <b>J01441A0006</b>
Ersatz für/ replaces <b>EWB40045-40</b>						
Original : DIN A4				Maße/ dimensions mm		
Blatt/ sheet 1 von/ of 1						



Maße/ dimensions mm

Original : DIN A4

Blatt/ sheet 1 von/ of 1