




- CONNECTOR DIMENSIONS ARE PER ARINC 600 SPECIFICATION.
- CONNECTOR IS SUPPLIED WITH CONTACTS AS LISTED IN TABLE.
- KEYING SHOWN IN POSITION "01" FOR ILLUSTRATION ONLY. CONNECTORS SHIPPED WITH KEYING INSTALLED IN POSITION PER TABLE. FOR POSITION "00" KEYING HARDWARE SHIPPED UNASSEMBLED.
- WITH CONTACTS FULLY SEATED TO REAR OF CAVITY.
- DUST COVER IS INCLUDED AND INSTALLED (NOT SHOWN).
- CONTACTS NOT SHOWN IN FRONT & REAR VIEWS FOR CLARITY.

COMPONENT	MATERIAL	FINISH
SHELL	DIE CAST ALUMINUM PER ASTM-B-85	CHROMATE CONVERSION PER MIL-C-5541, TYPE II, CLASS 3
INSERT RETENTION PLATES	ALUMINUM ALLOY PER ASTM-B-209	CHROMATE CONVERSION PER MIL-C-5541, TYPE II, CLASS 3
SCREWS	STEEL OR STAINLESS STEEL	STAINLESS STEEL OR PASSIVATED
POLARIZING KEYS	ZINC ALLOY PER ASTM-B-86	-
POLARIZING KEY RETAINING PLATE	ALUMINUM ALLOY PER ASTM-B-209	BLUE ANODIZED PER MIL-A-8625
12012 & 13C2 INSERTS	THERMOSET OR THERMOPLASTIC RESIN PER MIL-Q-24519	-
C4 INSERT	ALUMINUM ALLOY	ELECTROLESS NICKEL

"00"	MODULE A 211431-4 (SIZE 22 POSTED SOCKET CONTACT; QTY=118) 1445692-1 (SIZE 8 QUADRAx PIN CONTACT (NOT INSTALLED); QTY=2) MODULE B 446748-1 (SIZE 1 SMA CONTACT; QTY=4) MODULE C 1663767-2 (SIZE 20 FILLER PLUG; QTY=4) 1663767-3 (SIZE 16 FILLER PLUG; QTY=3) 448140-6 (SIZE 12 POSTED PIN CONTACT; QTY=4) 1484205-1 (SIZE 5 FILLER PLUG; QTY=2)	2157036-1
	CONTACTS & FILLER PLUGS INCLUDED AND INSTALLED EXCEPT AS NOTED	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE: 7-13-16	BY: C.C. THOMAS
DRAWN BY: C.C. THOMAS		DATE: 7-13-16	BY: C.C. THOMAS
CHECKED BY: C.C. THOMAS		DATE: 7-13-16	BY: C.C. THOMAS
APPROVED BY: C.C. THOMAS		DATE: 7-13-16	BY: C.C. THOMAS
CUSTOMER DRAWING		DATE: 7-13-16	BY: C.C. THOMAS

RCPT ASSY, SIZE 2, ARINC 600 (118Q2/C4/13C2)

00779 C-2157036

3:2 1 1 D