

Data sheet | Item number: 211-821

Marker; for Smart Printer; for use in nozzles; Length: 23 mm; white

www.wago.com/211-821



Data

Technical data

Marking method	Thermal transfer
Marking	plain

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Delivery form	Roll
Delivery form configuration	2,500 markers/reel
Printing device	Smart Printer (Thermal Transfer Printer)

Physical data

Depth	0.26 mm
Length	23 mm
Marking surface	4 x 23 mm

Mechanical Data

Mounting type	Pushing in
Smear resistance	in conjunction with 258-5005 Ink Ribbon

Material Data

Color	white
Material	Polyester
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	without adhesive
Halogen-free	Yes
Weight	220 g

Environmental requirements

Ambient temperature (storage)	+10 ... +22 °C
Ambient temperature (operation)	-20 ... +80 °C
Relative humidity	40 ... 50 %

Commercial data

Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-40-04-01
eCl@ss 9.0	27-40-06-29
ETIM 8.0	EC001530
ETIM 7.0	EC001530
PU (SPU)	1 pcs
Packaging type	box
Country of origin	DE
GTIN	4050821675006

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.

Customs tariff number

39269097900

Environmental Product Compliance

RoHS Compliance Status

Compliant, No Exemption

Optional accessories

Marking accessories

Marking sleeve

Item no.: 211-823

Nozzles; Length: 23 mm; For the use of 211-821; halogen-free; Cable outer diameter: 1.4 ... 5.0 mm; transparent

www.wago.com/211-823
Item no.: 211-824

Nozzles; Length: 23 mm; For the use of 211-821; halogen-free; Cable outer diameter: 5.0 ... 11.0 mm; transparent

www.wago.com/211-824
Item no.: 211-829

Nozzles; Length: 23 mm; For the use of 211-821; halogen-free; transparent

www.wago.com/211-829
Item no.: 211-922

Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 1.5 ... 2.5 mm; transparent

www.wago.com/211-922
Item no.: 211-923

Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 2.0 ... 4.0 mm; transparent

www.wago.com/211-923
Item no.: 211-924

Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 4.0 ... 7.0 mm; transparent

www.wago.com/211-924
Item no.: 211-925

Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 6.0 ... 10.0 mm; transparent

www.wago.com/211-925
Item no.: 211-926

Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 10.0 ... 14.0 mm; transparent

www.wago.com/211-926
Item no.: 211-927

Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 14.0 ... 22.0 mm; transparent

www.wago.com/211-927

Marking device

Item no.: 258-5000

Thermal transfer printer; Smart Printer; for complete control cabinet marking; 300 dpi; With marking material

www.wago.com/258-5000

Downloads

Documentation

Operating Instructions

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

211-821 Information on printing material

1
2020 年8月28 日

pdf
1.3 MB

[Download](#)

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 211-821

[URL](#)

[Download](#)

Marker; for Smart Printer; for use in nozzles; Length: 23 mm; white

Installation Notes

Marking



Remove the printed marker from the reel.



Slide the marker into the marking sleeve receptacle. Replacing the marker is also possible after the conductor has been terminated.



Slide the marker through the marker slot up to the end of the sleeve.



Then remove the rest of the card by twisting it off.

Subject to changes. Please also observe the further product documentation!