Woodhead[®] Standard Duty Cord Reels Now with 20A Ratings and CSA Approval

Woodhead standard duty cord reels, with 35 ft of 12/3 SJTOW cord, now have a 20A rating and are available with multiple end options, including connectors, quad boxes and duplex GFCI's. All models carry CSA listing.

Features and Benefits

Models available with 20A ratings. NEMA 5-20 plug is standard	Provides full 20A rating in a cost-effective indoor- rated reel. Eliminates need to specify industrial rated reels to get 20A ratings
Models available with locking plugs: either NEMA L5-20 or NEMA L5-15	Specified power supply outlets in ceilings utilize locking plugs to prevent disconnection. Factory- installed locking plugs eliminate the need for the installer to change the plugs to locking configurations
Reels complete with connectors, outlet boxes and GFCI ends are CSA listed	Eliminates need for field certifications for installations in Canada
Available with zero to four outlets	Flying leads allow users to install their own end effects. Factory installed connectors and outlet boxes help get these reels into use quickly
Powder-coated steel construction	Provides strength and durability to ensure long life
Simple ball-stop, tension and ratchet adjustment	Simplifies customization to a wide variety of applications

molex



Woodhead® 20A Cord Reel

Applications

Technical Schools / Colleges Maintenance Shops Warehouses Assembly Lines / Manufacturing Hospitals Data Centers



Technical School



Warehouse







Assembly Line

Woodhead® Standard Duty Cord Reels Now with 20A Ratings and CSA Approval



Specifications

REFERENCE INFORMATION CSA File No.: LR29921

ELECTRICAL Voltage: 120 VAC

ENVIRONMENTAL Enclosure Rating: NEMA 1

PHYSICAL

Construction: Powder coated steel Cord: All reels include 2 foot primary cord with plug and 35 ft of working cord, 12/3 SJTOW Working end: Includes a ball stop and may include a connector or outlet box Ratchet lock: Easily disengaged as needed Tension: Easily adjusted

Ordering Information

Order No.	Woodhead No.	Plug Type	Current Rating	Working End	No. of Outlets	GFCI Protected
1300910202	<u>998</u>	- NEMA 5-20	20A	Flying Leads		- No
1300910203	998-1533			NEMA 5-20 Connector	1	
1300910204	<u>998-3070G20</u>			Single Duplex GFCI Outlet Box: NEMA 5-20	2	Yes
1300910201	<u>998-3080</u>			Double Duplex Outlet Box: NEMA 5-20	4	No
1300910205	<u>998L</u>	NEMA L5-20: Locking	-20: Locking 20A	Flying Leads		No
1300910206	<u>998L-2747</u>			NEMA L5-20 Locking Connector	1	
1300910207	<u>998L-3070G20</u>			Single Duplex GFCI Outlet Box: NEMA 5-20	2	Yes
1300910208	<u>998L-1533</u>			NEMA 5-20 Connector	1	No
1300910209	<u>998L-3080</u>			Double Duplex Outlet Box: NEMA 5-20	4	
1300910085	<u>997</u>	- NEMA 5-15	15A	Flying Leads		No
1300910087	<u>997-1547</u>			NEMA 5-15 Connector	1	
1300910094	<u>997-3070G</u>			Single Duplex GFCI Outlet Box: NEMA 5-15	2	Yes
1300910090	<u>997-3000</u>			Double Duplex Outlet Box: NEMA 5-15	4	No
1300910210	<u>997L</u>	NEMA L5-15: Locking	15A	Flying Leads		No
1300910211	<u>997L-2547</u>			NEMA L5-15 Locking Connector	1	
1300910212	<u>997L-3070G</u>			Single Duplex GFCI Outlet Box: NEMA 5-15	2	Yes
1300910213	<u>997L-1547</u>			NEMA 5-15 Connector	1	- No
1300910214	<u>997L-3000</u>			Double Duplex Outlet Box: NEMA 5-15	4	

www.molex.com