

R 15-STI-C-0, 14-0,37 QMM



Image is for illustration purposes only. Please refer to product description.

Part number	09 15 000 6107
Specification	R 15-STI-C-0, 14-0,37 QMM
HARTING eCatalogue	https://b2b.harting.com/09150006107

Version

Gender	Male
Manufacturing process	Turned contacts

Technical characteristics

Conductor cross-section	0.14 ... 0.37 mm ²
Conductor cross-section	AWG 26 ... AWG 22
Operating current	≤10 A
Contact resistance	≤3 mΩ
Stripping length	8 mm
Mating cycles	≥500

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d



Pushing Performance
Since 1945

Material properties

California Proposition 65 substances Yes

California Proposition 65 substances Lead
Nickel

Specifications and approvals

Specifications IEC 60664-1
IEC 61984

Commercial data

Packaging size 100

Net weight 0.63 g

Country of origin Germany

European customs tariff number 85366990

GTIN 5713140021860

eCl@ss 27440204 Contact for industrial connectors