

product type designation

product description

IE TP Cord RJ45/RJ45, 4x2

Patch cable, preferred length, preassembled with two RJ45 connectors (10/100/1000/10000MB)

Industrial Ethernet TP Cord RJ45/RJ45, CAT 6A, TP cable 4x2, pre-assembled with 2 RJ45 connectors, length 30 m.



suitability for use

Easy connection of terminal devices to the IE FC cabling system

cable designation

LI 02YSCH 4x2x0,15 PIMF GN FRNC

wire length

30 m

electrical data

number of electrical connections

2

attenuation factor per length

- at 10 MHz / maximum
- at 100 MHz / maximum
- at 300 MHz / maximum
- at 600 MHz / maximum

0.086 dB/m
0.28 dB/m
0.501 dB/m
0.735 dB/m

impedance

- at 1 MHz ... 100 MHz
- at 10 MHz ... 600 MHz

100 Ω
100 Ω

relative symmetrical tolerance

- of the characteristic impedance at 1 MHz ... 100 MHz
- of the characteristic impedance at 10 MHz ... 600 MHz

15 %
10 %

transfer impedance per length / at 10 MHz

10 mΩ/m

loop resistance per length / maximum

290 mΩ/m

operating voltage

- RMS value

80 V

NVP value in percent

80 %

mechanical data

number of electrical cores

8

design of the shield

Overlapped aluminum-clad foil, sheathed in a braided screen of tinned copper wires

core diameter

- of AWG26 insulated conductor

0.5 mm

outer diameter

- of inner conductor
- of the wire insulation
- of cable sheath

0.5 mm
1 mm
6.2 mm


symmetrical tolerance of the outer diameter / of cable sheath

0.3 mm

material

- of the wire insulation

polyethylene (PE)

| | |
|---|--|
| <ul style="list-style-type: none"> of cable sheath | FRNC |
| color | |
| <ul style="list-style-type: none"> of the insulation of data wires of cable sheath | white/blue, white/orange, white/green, white/brown green |
| bending radius | |
| <ul style="list-style-type: none"> with single bend / minimum permissible with multiple bends / minimum permissible | 31 mm 43.5 mm |
| weight per length | 50 kg/km |
| ambient conditions | |
| ambient temperature | |
| <ul style="list-style-type: none"> during operation during storage during transport during installation note | -25 ... +80 °C -25 ... +80 °C -25 ... +80 °C -25 ... +80 °C In fixed installation -40 °C to 80 °C |
| fire behavior | flame resistant according to IEC 60332-1-2, smoke density according to IEC 61034 |
| class of burning behaviour / according to EN 13501-6 | Eca |
| chemical resistance | |
| <ul style="list-style-type: none"> to mineral oil to grease | oil resistant according to IEC 60811-2-1 (4 h / 70°C) Conditional resistance |
| radiological resistance / to UV radiation | not resistant |
| protection class IP | IP20 |
| product features, product functions, product components / general | |
| product feature | |
| <ul style="list-style-type: none"> halogen-free silicon-free | Yes Yes |
| standards, specifications, approvals | |
| UL/ETL listing / 300 V Rating | No |
| UL/ETL style / 600 V Rating | Yes; E130266 AWM STYLE 21279 |
| certificate of suitability | |
| <ul style="list-style-type: none"> EAC approval UL approval RoHS conformity | Yes Yes Yes |
| standard for structured cabling | Cat6A |
| Marine classification association | |
| <ul style="list-style-type: none"> American Bureau of Shipping Europe Ltd. (ABS) French marine classification society (BV) Det Norske Veritas (DNV) Germanische Lloyd (GL) Lloyds Register of Shipping (LRS) Nippon Kaiji Kyokai (NK) Polski Rejestr Statkow (PRS) | No No No No No No No |
| reference code | |
| <ul style="list-style-type: none"> according to IEC 81346-2 according to IEC 81346-2:2019 | WG WGB |
| further information / internet-Links | |
| Internet-Link | |
| <ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Selection guide for cables and connectors to website: Image database to website: CAx-Download-Manager to website: Industry Online Support | http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdlxcP http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com |
| last modified: | 6/25/2022  |