1977886-1 ✓ ACTIVE

AMP | AMP CPC

TE Internal #: 1977886-1

Circular Power Connectors, Housing, 600 VDC, Wire-to-Wire, 37 Position, Sealable, Wire & Cable, Receptacle, Pin, Signal, Black, All

Plastic, AMP CPC

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors > One-Piece Connector, Sealed, CPC Series 1











Connector Product Type: Housing

Operating Voltage: 600 VDC

Connector System: Wire-to-Wire

Number of Positions: 37

Sealable: Yes

All One-Piece Connector, Sealed, CPC Series 1 (33)

Features

Product Type Features

Connector Seal & Plug Type	Peripheral, Wire Entry Seal
Connector Product Type	Housing
Connector System	Wire-to-Wire
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Receptacle
Circular Connector Shell Type	All Plastic

Configuration Features

Reverse Numbering	Without
Number of Positions	37
Number of Power Positions	0
Number of Signal Positions	37



Electrical Characteristics

Liectifical Characteristics	
Operating Voltage	600 VAC
Contact Features	
Reverse Gender	No
Contact Type	Pin
Contact Protection	With
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Alignment	With
Panel Mount Feature Type	Flange
Mating Retention Type	Threaded Coupling
Thread Size	1 3/18-18 UNEF-2A
Polarization Code	A
Mating Retention	With
Panel Mount Feature	Without
Housing Features	
Body Orientation	Straight
Housing Color	Black
Housing Material	Nylon (UV Resistant)
Housing Material Circular Connector Shell Size	Nylon (UV Resistant) 23
Circular Connector Shell Size	
Circular Connector Shell Size Usage Conditions	23
Circular Connector Shell Size Usage Conditions Operating Temperature Range	23 -55 - 105 °C[-67 - 221 °F]
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance	23 -55 – 105 °C[-67 – 221 °F]
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application	23 -55 – 105 °C[-67 – 221 °F] Immersion
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application	23 -55 – 105 °C[-67 – 221 °F] Immersion Signal
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded	23 -55 – 105 °C[-67 – 221 °F] Immersion Signal
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards	23 -55 – 105 °C[-67 – 221 °F] Immersion Signal No
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards UL Flammability Rating	23 -55 – 105 °C[-67 – 221 °F] Immersion Signal No
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards UL Flammability Rating Packaging Features	23 -55 – 105 °C[-67 – 221 °F] Immersion Signal No UL 94V-0



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













TE Part # 208680-1 SEALING CAP ASSY,SZ 23,CPC



TE Part # 1977887-1 PLUG.ASSY,23-37STD SEX THRD AD, **UV RESIS**



TE Part # 208337-1 SEAL PROTECTOR PIN



CAP, CPC, SIZE 23 RECP, ORANGE



TE Part # 6-2407269-2 CAP, CPC, SIZE 23 RECP, BLACK



TE Part # 6-2407269-3 CAP, CPC, SIZE 23 RECP, RED



CAP, CPC, SIZE 23 RECP, YELLOW

Also in the Series | AMP CPC







Circular Connector Caps & Covers(16) Circular Connector Hardware(3)



Circular Connector Keying Plugs(2)



Circular Power Connectors(459)



Connector Backshells(56)



Connector Seals & Cavity Plugs(36)



Connector Strain Relief(6)



Insertion & Extraction Tools(1)



Power Contacts(6)



Sealing Sleeves(2)

Customers Also Bought

















Documents

Product Drawings

RCPT.ASSY,23-37STD SEX FREE HG, UV RESIS

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1977886-1_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1977886-1_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1977886-1_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Product Specifications

Product Specification

English