| $ \begin{array}{c c c c c c c c c c c c c c c c c c c $   | 1 | 2             | 3   | 4  | 5  |      |    |
|---|---|---------------|---|--|--|------|----|
| G    Image: Constraint of the constraint          |   | Dim L         | 3.54 Dim B<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0 | 3.54    TECHNICAL CHARAC      MATERIAL    INSULATOR: PA 66      FLAMMABILITY RATH    COLOR: GREEN      COLOR: GREEN    CONTACT PIN: BRAS      SURFACE OF SOLDE    ENVIRONMENTAL      OPERATING TEMPEF    COMPLIANCE: LEAD      ELECTRICAL    CURRENT RATING:      WORKING VOLTAGE:    WORKING VOLTAGE:      WORKING VOLTAGE:    WITHSTANDING VOL      CONTACT RESISTAN    SALSE CERTIFIED E31      MECHANICAL    PITCH: 5.08mm      SOLDERING    JEDEC LEAD FREE V      PACKAGING    BOX      N=NUMBER OF CONTACTS    TO      DIM    TO      UIM    TO      DIM    TO      UIN L    (N-1)×5.08+7.08    ±0.15      ±0.15    ±0.25 | TERISTICS<br>NG: UL94-V0<br>S (CuZn)<br>R TAIL PLATING: TIN<br>RATURE: -40 UP TO 105°C<br>FREE AND ROHS<br>UL<br>20A<br>300VAC<br>TAGE: 1.6KV<br>CE: 20 mOhm MAX<br>5414<br>VAVE SOLDERING PROCESS<br>DL<br>2636P 3848P<br>$\pm 0.35$ $\pm 0.40$ | -    |    |
| F    Image: Second sec         |   | PROJECTION:   | GENERAL TOLERANCE   |  |  |      |    |
| D   | F |               | .X = <sup>+</sup> /_ 0.2  |  |  | Ļ    |    |
| C      Image: Constraint of the state of the sta |   |               | .XX = <sup>+</sup> /_ 0.15  |  |  |      |    |
| B      07-JUL-15      UPDATE      AK        A      15-JUN-10      PDF      JP        SHEET: 1/2      WERI PART NO: 691 331 510 0xx      A4  |   | APPROVAL: FBr | UNIT: MM  |  |  | SIZE | ام |
|   |   |               |   |  | iL   | 1 1  | 5  |
| REV DATE FILE BY DRAW: MARVIN   |   | JP<br>BY      | SHEET: 1/2<br>DRAW: MARVIN  | WERI PART NO: 691 331 510 0xx  |  |      |    |

| 1 | 2 | 3 | 4 | 5 | - |
|---|---|---|---|---|---|
|   |   |   |   |   | _ |

А

В

С

## **Cautions and Warnings:**

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

| R   | toHS Compliant |      |    |              |                            |                          |           |   |
|-----|----------------|------|----|--------------|----------------------------|--------------------------|-----------|---|
| G   |                |      |    | PROJECTION:  | GENERAL TOLERANCE          |                          |           | 1 |
| F   |                |      |    |              | .X = <sup>+</sup> /_ 0.2   |                          |           |   |
| E   |                |      |    |              | .XX = <sup>+</sup> /_ 0.15 |                          |           |   |
| D   |                |      |    |              |                            | WÜRTH ELEKTRONĬK         |           |   |
| С   |                |      |    | APPROVAL: JC | UNIT: MM                   | DESCRIPTION: DISCLAIMER  | SIZE      | Ъ |
| В   |                |      |    |              | SCALE:                     |                          |           | Р |
| A   | 10-SEP-14      | PDF  | QL |              | SHEET: 2/2                 | WERI PART NO: DISCLAIMER | <b>A4</b> |   |
| REV | DATE           | FILE | BY |              | DRAW: QL                   |                          |           |   |