



ELECTRONICS, INC.  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089  
<http://www.nteinc.com>

## NTE30053 thru NTE30059 Super Bright LED Indicators, 8mm

**Features:**

- RoHS Compliant
- All Plastic Mold Type w/Water Clear Lens:
  - NTE30053 (Yellow Green, AlInGaP/GaAs)
  - NTE30054 (Light Green, InGaN/GaN)
  - NTE30055 (Orange, AlInGaP/GaAs)
  - NTE30056 (Light Red, AlInGaP/GaAs)
  - NTE30057 (Deep Red)
  - NTE30058 (Blue, INGaN/GaN)
  - NTE30059 (White)

**Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Reverse Voltage, $V_R$	
NTE30054, NTE30058, .....	4V
All Others .....	5V
Continuous Forward Current, $I_F$	
NTE30055, NTE30056 .....	20mA
NTE30057, NTE30059 .....	30mA
All Others .....	25mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width), $I_{FM}$	
NTE30053 .....	50mA
NTE30054, NTE30055, NTE30056, NTE30057, NTE30058, .....	100mA
NTE30059 .....	150mA
Power Dissipation, $P_D$	
NTE30053, NTE30055, NTE30056, NTE30057 .....	100mW
NTE30054, NTE30058, .....	120mW
NTE30059 .....	150mW
LED Junction Temperature, $T_j$ .....	+100°C
Operating Temperature Range, $T_{opr}$	
NTE30055, NTE30056, NTE30057, NTE30059 .....	-20°C to +80°C
All Others .....	-25°C to +85°C
Storage Temperature Range, $T_{stg}$	
NTE30053 .....	-25°C to +100°C
NTE30055, NTE30056, NTE30057, NTE30059 .....	-30°C to +100°C
NTE30054, NTE30058 .....	-40°C to +100°C
Lead Temperature (During Soldering, .063 (1.6mm) from body, 5sec max), $T_L$ .....	+260°C

Rev. 1-22



**Electro-Optical Characteristics:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage NTE30053	$V_F$	$I_F = 20\text{mA}$	-	2.2	2.5	V
NTE30054			-	3.5	4.0	V
NTE30055, NTE30056			2.0	-	2.2	V
NTE30057			2.0	1.86	2.2	V
NTE30058			-	3.5	4.0	V
NTE30059			3.0	-	3.2	V
Reverse Current NTE30053	$I_R$	$V_R = 5\text{V}$	-	-	10	$\mu\text{A}$
NTE30054, NTE30058, NTE30059		$V_R = 4\text{V}$	-	-	60	$\mu\text{A}$
Luminous Intensity NTE30053	$I_V$	$I_F = 20\text{mA}$ , Note 1	600	1600	-	mcd
NTE30054			2000	4500	-	mcd
NTE30055, NTE30056			3000	3500	4000	mcd
NTE30057			2000	-	2500	mcd
NTE30058			700	1500	-	mcd
NTE30059			10000	-	12000	mcd
Peak Emission Wave Length NTE30053	$\lambda_P$	$I_F = 20\text{mA}$	-	575	-	nm
NTE30054			-	523	-	nm
NTE30055			585	590	595	nm
NTE30056			620	625	-	nm
NTE30057			655	660	665	nm
NTE30058			-	468	-	nm
NTE30059			7000	-	9000	K
Dominate Wave Length NTE30053	$\lambda_d$ (HUE)	$I_F = 20\text{mA}$ , Note 2	568	572	576	nm
NTE30054			520	525	540	nm
NTE30058			463	470	479	nm
Spectral Line Half Width NTE30053	$\Delta\lambda$	$I_F = 20\text{mA}$	-	15	-	nm
NTE30054			-	45	-	nm
NTE30058			-	35	-	nm
Viewing Angle NTE30053	$2\theta^{1/2}$	$I_F = 20\text{mA}$	-	25	-	deg.
NTE30058			-	35	-	deg.
All Others			-	30	-	deg.
Terminal Capacitance (NTE30053 <b>Only</b> )	$C_t$	$V = 0\text{V}$ , $f = 1\text{MHz}$	-	35	-	$\text{pF}$
Response Frequency (NTE30053 <b>Only</b> )	$F_c$		-	4	-	MHz
Optic Rise Time (NTE30054 <b>Only</b> )	$\tau$	$I_F = 20\text{mA}$	-	30	-	ns

Note 1. Luminous intensity is measured with an Exeltron 2001.

Note 2. The dominate wavelength,  $\lambda_d$ , is derived from the CIE Chromaticity Diagram and represents the color of the device.

