

## **GENERAL SPECIFICATIONS:**

RATING: 10A / 125V AC CABLE TYPE / SIZE: **SVT. 18 AWG X 3 TEMPERATURE RATING:** 60° C MIN.

CONDUCTOR COLORS: BLACK / WHITE / GREEN

CABLE JACKET COLOR: **BLACK** 

OVERALL LENGTH (L): 1730+ 20 MM (5 Ft, 8 INCH)


CABLE OUTER DIAMETER: 6.3 + 0.1 MMEND 'A' TERMINATION: **NEMA 5-15P** END 'B' TERMINATION: IEC 320 / C5 APPROVALS PLUG: UL. CSA or cUL APPROVALS CABLE: UL, CSA or cUL APPROVALS CONNECTOR: UL. CSA or cUL

## PACKING:

HANKING

L = 200 + 10 MM





## NOTES:

1. CORD. PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



prior notice



NO.			
			Т
			NCES: ANGULAR
		+/- 0.1 +/005	+/- 1°

PART NO

REV.

DASH

INIT.BY: SO

DRAWN: NF

TA	ABULATION BLOCK
S: LAR I°	GlobTek, Inc.

186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111

Contents of this document are subject to change withou

Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL,CSA or EN Standards for proper installation instruction.

Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

ANGULAR www.globtek.com MILLIMETERS ANGULAR DATE: DWG TITLE: NORTH AMERICAN DETACHABLE CORDSET .xx +/- 0.3 09/06/07 xxx +/= 013 DATE: FSCN No.: SIZE REV. MODEL: N/AG, CC Α 09/06/07

DESCRIPTION

DATE: APRVD: HM SCALE: NONE 09/06/07

PART NO: 3021455F8712(R)

Complies with

Requirements of Californi

SHEET 1/1

NOTES