


PART NUMBER	WIRE INSNL. RANGE		DIM. CRIMP-RANGES				PARTS/ REEL	CRIMP TYPE
	mm ²	Ømm	B1	H1 ± 0.3	B2	H2 ± 0.4		
90020-X1XX	0.5-1.5	2.0-3.3	3.0	3.25	4.0	4.7	4000	A
90020-X2XX	0.5-1.5	1.4-2.3	3.0	3.25	3.6	3.6	5000	A
90020-X3XX	1.0-2.5	2.7-4.3	3.5	3.85	4.8	5.5	3500	A
90020-X4XX	1.0-2.5	1.8-2.9	3.5	3.85	4.3	4.1	4000	A
90020-X5XX	0.5-1.0	1.4-2.3	2.6	2.8	3.6	3.7	5000	B

⇒
⇒
⇒
⇒ FOR REDUCED INSULATION THICKNESS


	MATERIAL	PLATING
90020-XX02	PH. BRONZE	HOT TIN DIP. (0.8-2.5 µm)

CRIMP AREA OPEN ON THE TOP




REELING DIRECTION FOR FINISHED PARTS
PART No. 90020-0XXX

CRIMP AREA OPEN ON THE BOTTOM



REELING DIRECTION FOR FINISHED PARTS
PART No. 90020-1XXX

CODE: PART-NO.



MODIFY DIMENSIONS	EC NO: DRWIN:DCARTON 2009/03/26 CHKD: APPR:	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	SCALE METRIC	DESIGN UNITS METRIC	FIRST ANGLE PROJECTION	REVISE ON CAD ONLY											
		▽ - 0 ▽ - 0	<table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>3 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>2 PLACES</td> <td>± 0.1</td> <td>± ---</td> </tr> <tr> <td>1 PLACE</td> <td>± 0.2</td> <td>± ---</td> </tr> </tbody> </table> ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		mm	INCH	4 PLACES	± ---	± ---	3 PLACES	± ---	± ---	2 PLACES	± 0.1	± ---	1 PLACE	± 0.2	± ---
	mm	INCH																
4 PLACES	± ---	± ---																
3 PLACES	± ---	± ---																
2 PLACES	± 0.1	± ---																
1 PLACE	± 0.2	± ---																
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						A2												