

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

Features

- Halogen free available upon request by adding suffix "-HF"
- High Voltage
- Low Leakage
- Low Forward Voltage Drop
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)

Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C

	Microsemi Catalog Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
ł	R2500	R2500	2500V	1750V	2500V
ſ	R3000	R3000	3000V	2100V	3000V


Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I _{F(AV)}	200mA	T _A = 50°C
Peak Forward Surge Current	I _{FSM}	30A	8.3ms, half sine
Maximum Instantaneous Forward Voltage R2500 R3000	V _F	3.0V 4.0V	I _{FM} = 0.5A; T _A = 50°C
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	5.0μΑ 50μΑ	T _A = 25°C T _A = 100°C
Typical Junction Capacitance	CJ	30pF	Measured at 1.0MHz, V _R =4.0V

Note: 1. High Temperature Solder Exemptions Applied, see EU Directive Annex 7.

R2500 THRU R3000

200 Milliamp High Voltage Silicon Rectifier 2500 to 3000 Volts



DIMENSIONS							
	INCHES		ММ				
DIM	MIN	MAX	MIN	MAX	NOTE		
А	.230	.300	5.80	7.60			
В	.104	.140	2.60	3.60			
С	.026	.034	.70	.90			
D	1.000		25.40				
D	1.000		25.40				


-www.mccsemi.com

R2500 - R3000




Figure 1 Typical Reverse Characteristics 4 2 1 .8 .6 .4 .2 μΑ .1 .08 .06 .04 ТJ = 25°C .02 .01 80 100 40 60 20 120 0 Volts

Micro Commercial Components



Average Forward Rectified Current - Amperes/ersus Ambient Temperature $\ -^\circ C$





-www.mccsemi.com

Instantaneous Reverse Current - Micro Ampsversus Percent Of Rated Peak Reverse Voltage - Volts



Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 4Kpcs/Reel
Part Number-AP	Ammo Packing: 3Kpcs/Ammo Box
Part Number-BP	Bulk: 25Kpcs/Carton

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com