

## Base strip - MDSTB 2,5/ 9-G-5,08 - 1842584

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Header, Nominal current: 10 A, Rated voltage (III/2): 320 V, Number of positions: 9, Pitch: 5.08 mm, Color: green, Contact surface: Tin, Assembly: Soldering, Can be aligned! Mounting flange: Order No. 1736771, 1736768. In combination with MVSTB or FKCV plug components, both an MVSTBW (or FKCVW) and an MVSTBR plug (or FKCVR) must be used. Combination with TMSTBP plug components is not possible!

The figure shows a 10-pos. version with 20 contacts

### Product Features

- Plug-in direction parallel to the PCB
- Double-level header with offset levels
- High contact density
- Improved view and access to lower level
- Add-on ejectors for high-pos. connectors should be mounted to the left and right



### Key commercial data

|                                      |           |
|--------------------------------------|-----------|
| Packing unit                         | 1 pc      |
| Weight per Piece (excluding packing) | 14.78 GRM |
| Custom tariff number                 | 85366990  |
| Country of origin                    | Germany   |

### Technical data

#### Dimensions

|                |          |
|----------------|----------|
| Length         | 22.1 mm  |
| Pitch          | 5.08 mm  |
| Dimension a    | 40.64 mm |
| Pin dimensions | 1 x 1 mm |
| Hole diameter  | 1.4 mm   |

#### General

|                           |                |
|---------------------------|----------------|
| Range of articles         | MDSTB 2,5/..-G |
| Insulating material group | I              |

## Base strip - MDSTB 2,5/ 9-G-5,08 - 1842584

### Technical data

#### General

|                                  |        |
|----------------------------------|--------|
| Rated surge voltage (III/3)      | 4 kV   |
| Rated surge voltage (III/2)      | 4 kV   |
| Rated surge voltage (II/2)       | 4 kV   |
| Rated voltage (III/3)            | 250 V  |
| Rated voltage (III/2)            | 320 V  |
| Rated voltage (II/2)             | 400 V  |
| Connection in acc. with standard | EN-VDE |
| Nominal current I <sub>N</sub>   | 10 A   |
| Maximum load current             | 10 A   |
| Insulating material              | PBT    |
| Color                            | green  |
| Number of positions              | 9      |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

## Base strip - MDSTB 2,5/ 9-G-5,08 - 1842584

### Approvals

#### Approvals

---

#### Approvals

CSA / UL Recognized / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / GOST / IECCEB Scheme / GOST / CCA / cULus Recognized

---


#### Ex Approvals


---


#### Approvals submitted

---

### Approval details

|  |       |       |
|--|-------|-------|
| CSA  |       |       |
|  | B     | D     |
| Nominal current IN   | 15 A  | 15 A  |
| Nominal voltage UN   | 300 V | 300 V |

|   |       |       |
|---|-------|-------|
| UL Recognized  |       |       |
|   | B     | D     |
| Nominal current IN  | 15 A  | 10 A  |
| Nominal voltage UN  | 300 V | 300 V |

|   |       |
|---|-------|
| VDE Gutachten mit Fertigungsüberwachung  |       |
| Nominal current IN  | 10 A  |
| Nominal voltage UN  | 250 V |

# Base strip - MDSTB 2,5/ 9-G-5,08 - 1842584

## Approvals

|                                |       |       |
|--------------------------------|-------|-------|
| cUL Recognized                 |       |       |
|                                | B     | D     |
| Nominal current I <sub>N</sub> | 15 A  | 10 A  |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V |

|      |  |
|------|--|
| GOST |  |
|------|--|

|                                |       |
|--------------------------------|-------|
| IECEE CB Scheme                |       |
| Nominal current I <sub>N</sub> | 10 A  |
| Nominal voltage U <sub>N</sub> | 250 V |

|      |  |
|------|--|
| GOST |  |
|------|--|

|                                |       |
|--------------------------------|-------|
| CCA                            |       |
| Nominal current I <sub>N</sub> | 10 A  |
| Nominal voltage U <sub>N</sub> | 250 V |

|                  |  |
|------------------|--|
| cULus Recognized |  |
|------------------|--|

## Drawings

## Base strip - MDSTB 2,5/ 9-G-5,08 - 1842584

Dimensioned drawing

