











REV

A1

A2

ECO



NOTES: UNLESS OTHERWISE SPECIFIED

- MATERIAL: HOUSING, END CAP, WEDGE: THERMOPLASTIC SEALS: SILICONE RUBBER
- 2. MODIFICATIONS: END CAP, SOLID SEAL, GOLD CONTACTS, RESISTOR, WEDGE AWM-2S, LASER MARKING, COLOR.
- 3. SPECIFICATIONS: 3.1 CURRENT RATING: 7.5 AMPS 3.2 OPERATING TEMPERATURE: -55°C TO +125°C 3.3 CONTACT SIZE: 20
 - 3.4 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT

SOLID REAR SEAL

- 4. MATING PART: ATM04-2P* RECEPTACLE (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

PART NUMBER CHART				
COLOR	PART NUMBER			
GREY	ATM06-2S-R120GRY			
BLACK	ATM06-2S-R120BLK			
BLUE	ATM06-2S-R120BLU			
BROWN	ATM06-2S-R120BRN			
GREEN	ATM06-2S-R120GRN			
RED	ATM06-2S-R120RED			
WHITE	ATM06-2S-R120WHT			
YELLOW	ATM06-2S-R120YEL			

	SE	E CHART	REI	F: DTM06-2S-P006		. !		
	PART N	IUMBER		DESCRIPTION	ITEM	-		
QUANTITY	MATERIALS LIST							
1) All dimensions a 2) Tolerances are a	as follows:	SIGNATURE DRAWN: JAH	23MAY2017	Amphenol				
1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 3) Note reference	Fractions ±1/64 Angles ±1°	CHECKED: ENGINEER: APPROVAL:		Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036	_			
MATERAL SPECIFICATIONS: CUSTOMER THIS DRAWING IS SUPPLET FROCESS SPECIFICATIONS: SPECIFICATIONS: SPECIFICATIONS AND DEED THE AMPIENCAL CORPORA OPERATIONS AND EAST OPERAT				PLUG, 2-WAY ATM, 120 OHM, 1/2W				
		IGN FEATURES, RFORMANCE DATA E PROPERTY OF ATION. NO RIGHTS MPLIED. ALL	B C- ATM06-2S-R120XXX	EVISION A2				
NEXT ASS'Y:		MANUFACTURING VARIATIONS.		SCALE: NONE SHEET 1 OF	1			

END CAP MATCHES

CONNECTOR COLOR -

SEE CHART FOR

CONNECTOR BODY COLOR

REVISIONS

DATE

23MAY2017

16APR2018

BY

JAH

JAH

APPR

DESCRIPTION

RELEASE

CHANGED TO CHARTED DRAWING

PLUG, 2-WAY ATM, 120 OHM, 1/2W

ATM06-2S-R120XXX REV: A2 SH