

10	9	8	7	6	5	4	3	2	1	
LOOSE PIECE MAT'L NO.	LOOSE PIECE ENGRNG NO.	CONTINUOUS STRIP MAT'L NO.	CONTINUOUS STRIP ENGRNG NO.	TAPE MAT'L NO.	TAPE ENGRNG NO.	FITS MALE TAB SIZE	"A" MAX	"C" MAX	"E" MAX	"H" NOMINAL
190030132	BB-2207V	190030134	BB-2207VC	190030133	BB-2207VT	.187 X .020	.78 (19.8)	.316 (8.03)	.170 (4.32)	1.38 (35.1)
190030135	BB-2208V	190030137	BB-2208VC	190030136	BB-2208VT	.187 X .032	.78 (19.8)	.316 (8.03)	.170 (4.32)	1.38 (35.1)
190030044	BB-2206VB	190030045	BB-2206VBC	190030080	BB-2206VBT	.250 X .032	.86 (21.8)	.380 (9.65)	.180 (4.57)	1.42 (35.6)

B1

CONTINUOUS PLASTIC STRIP

NEMA DETENT LOCATION PER UL310

Ø .083
[2.11]

"C"

"H" ±.03(0.8)

TERMINAL CUT-OFF LOCATION, MAY PROTRUDE FROM HOUSING

PARTS ON TAPE

Ø 0.160 MWID
[4.06]

WIRE STOP

"E"

"A"

B1

- NOTE(S):
- MATERIAL:
 TERMINAL: BRASS .016/ 0.41
 PLATING: ELECTRO-TIN
 INSULATION: NYLON 6/6 94V-0 RATING
 COLOR: BLUE
 - MWID = MAXIMUM WIRE INSULATION DIAMETER.
 - PRODUCT SPECIFICATION: PS-19902-008
 - PARTS ARE RoHS COMPLIANT.

SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: ADD TERM CUTOFF NOTE				
	DIMENSION UNITS	SCALE					
▽ = 0	IN/MM	NTS	EC NO: 607062		FIQD FEMALE, INSULKRIMP		
▽ = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRWN: DMYRICK 2018/11/02		94V-0 MATERIAL 16-14 AWG		
▽ = 0			CHK'D: JMACNEIL 2018/11/02		PRODUCT CUSTOMER DRAWING		
▽ = 0	4 PLACES ±	±	APPR: JMACNEIL 2018/11/02		DOCUMENT NUMBER		
▽ = 0	3 PLACES ±	0.25 ± 0.005	INITIAL REVISION:		SD-19003-002		
▽ = 0	2 PLACES ±	0.13 ± 0.01	DRWN: HBEITZEL 2001/06/11		DOC TYPE DOC PART REVISION		
▽ = 0	1 PLACE ±	±	APPR: RDEROSS 2001/06/11		PSD 001 B1		
▽ = 0	0 PLACES ±	±	ANGULAR TOL ± 0.5°		MATERIAL NUMBER CUSTOMER SHEET NUMBER		
▽ = 0	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		SEE CHART GENERAL MARKET 1 OF 1		
▽ = 0			DRAWING SERIES		B-SIZE 19003		