



- NOTES:
- MATERIAL:
HOUSING: LCP G.F. UL94 V-0, COLOUR BLACK.
TERMINAL: PHOSPHUR BRONZE PLATED WITH 0.00005 MIN GOLD FLASH, OVER 0.0010 MIN PALLADIUM NICKEL IN CONTACT AREA, BOTH OVER 0.00127 MIN NICKEL OVERALL.
 - JACK FOR MATING WITH IEC 60603-7 & TIA 1096 PLUGS (95043 MOLEX SERIES)
 - PRODUCT SPECIFICATION: PS-85508-0001
 - PACKAGING SPECIFICATION: T.B.D.
 - COPLANARITY OF SIGNAL LEADS: 0.10MAX
 - EXCEEDS CATEGORY 5E PERFORMANCE
 - RECOMMENDED PCB THICKNESS 1.57

LAST INSPECTION NUMBER USED: 13

MOD SOLDER TAILS	EC NO: IPG2013-1552	2013/04/08
DRWN:DBYRNES	2013/05/10	
CHKD:DMAHER	2013/06/05	
APPR:STGRIFFIN		

QUALITY SYMBOLS	DESCRIPTION
▽=0	
∇=0	

GENERAL TOLERANCES (UNLESS SPECIFIED)	mm	INCH
	4 PLACES ± ---	± ---
	3 PLACES ± ---	± ---
	2 PLACES ± 0.15	± ---
	1 PLACE ± 0.25	± ---
	ANGULAR ± 2 °	

DRAWN BY		DATE	TITLE
DBYRNES		2012/02/23	CAT5E TOP ENTRY SHIELDED SMT
CHECKED BY		DATE	
DMAHER			
APPROVED BY		DATE	MOLEX INCORPORATED
STGRIFFIN		2012/10/26	
MATERIAL NO.		DOCUMENT NO.	
93326-0001		SD-93326-001	

DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
MM ONLY	5:1	METRIC	☉
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SHEET NO. 1 OF 1	
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			