

## Flush-type connector - SACC-DSIP-M12MSB-5CON-L180-SI - 1528264

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Sensor/actuator flush-type plug, 5-pos., M12, B-coded, front/press-in mounting, with straight solder connection



### Key commercial data

Packing unit	1 1
Minimum order quantity	10 1
Weight per Piece (excluding packing)	22.6 GRM
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Ambient conditions

Degree of protection	IP67
----------------------	------

#### General

Rated current at 40°C	4 A
Rated voltage	60 V
Number of positions	5
Contact resistance	≤ 0.003 Ω
Insulation resistance	≥ 1 TΩ
Coding	B - inverse
Status display	No
Surge voltage category	II
Pollution degree	3
Connection method	Solder pins

#### Material

Inflammability class according to UL 94	V0
---	----

## Flush-type connector - SACC-DSIP-M12MSB-5CON-L180-SI - 1528264

### Technical data

#### Material

Contact material	CuZn
Contact surface material	Au
Contact carrier material	PBT
Material, knurls	Nickel-plated brass
Sealing material	NBR

### Classifications

#### eCl@ss

eCl@ss 4.0	27140815
eCl@ss 4.1	27140815
eCl@ss 5.0	27143423
eCl@ss 5.1	27143423
eCl@ss 6.0	27143423
eCl@ss 7.0	27449001
eCl@ss 8.0	27449001

#### ETIM

ETIM 2.0	EC001297
ETIM 3.0	EC002061
ETIM 4.0	EC002062
ETIM 5.0	EC002062


#### UNSPSC

UNSPSC 6.01	31251501
UNSPSC 7.0901	31251501
UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	31251501

### Drawings

## Flush-type connector - SACC-DSIP-M12MSB-5CON-L180-SI - 1528264

Schematic diagram



Pin assignment M12 male connector, 5-pos., B-coded, male side