## SIEMENS

## Data sheet

## 3SU1001-6AA00-0AA0-Z Y19



Indicator light, 22 mm, round, plastic, amber, lens, smooth, with laser labeling, inscription or symbol Customer-specific selection with SIRIUS ACT configurator (CIN)

| product brand name   | SIRIUS ACT   |
|--|--|
| product designation  | Indicator lights   |
| design of the product  | Actuating/signaling element  |
| product type designation   | 3SU1   |
| product line   | Plastic, black, 22 mm  |
| Actuator   |  |
| product extension optional   |  |
| light source   | Yes  |
| contact module   | No   |
| color  |  |
| <ul> <li>of the actuating element</li> </ul>                       | amber  |
| material of the actuating element                                  | plastic  |
| shape of the actuating element                                     | round  |
| outer diameter of the actuating element                            | 29.45 mm   |
| marking of the actuating element                                   | Any inscription, text or symbol, can only be ordered via SIRIUS ACT configurator/Configuration Identification Number (CIN) |
| Front ring   |  |
| product component front ring                                       | No   |
| General technical data   |  |
| protection class IP  | IP66, IP67, IP69(IP69K)  |
| degree of protection NEMA rating                                   | 1, 2, 3, 3R, 4, 4X, 12, 13   |
| shock resistance   |  |
| <ul> <li>according to IEC 60068-2-27</li> </ul>                    | sinusoidal half-wave 15g / 11 ms   |
| <ul> <li>for railway applications according to EN 61373</li> </ul> | Category 1, Class B  |
| vibration resistance   |  |
| <ul> <li>according to IEC 60068-2-6</li> </ul>                     | 10 500 Hz: 5g  |
| <ul> <li>for railway applications according to EN 61373</li> </ul> | Category 1, Class B  |
| reference code according to IEC 81346-2                            | Р  |
| Substance Prohibitance (Date)                                      | 10/01/2014   |
| Connections/ Terminals   |  |
| tightening torque of the screws in the bracket                     | 1 1.2 N·m  |
| Ambient conditions   |  |
| ambient temperature  |  |
| during operation   | -25 +70 °C   |
| <ul> <li>during storage</li> </ul>                                 | -40 +80 °C   |
| environmental category during operation according to IEC 60721     | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)   |
| Installation/ mounting/ dimensions                                 |  |
| height   | 29.5 mm  |
|  |  |

| width                                       | 29.5 mm |
|---|---------|
| shape of the installation opening           | round   |
| mounting diameter                           | 22.3 mm |
| positive tolerance of installation diameter | 0.4 mm  |
| mounting height                             | 11.8 mm |
| installation width                          | 29.5 mm |
| installation depth                          | 24.4 mm |
| Certificates/ approvals                     |         |
| Further information                         |         |

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-6AA00-0AA0-Z Y19

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-6AA00-0AA0-Z Y19

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-6AA00-0AA0-Z Y19

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1001-6AA00-0AA0-Z Y19&lang=en

last modified:

1/27/2022 🖸