

1364839

https://www.phoenixcontact.com/us/products/1364839

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Mounting panel for WIL-SHM-S SENSOR (see "Accessories" tab).

Product description

The mounting panel is required to mount the WIL-SHM-S SENSOR in the rotor blade of a wind turbine generator. The mounting panel is affixed inside the rotor blade using a suitable adhesive. The sensor is attached to the mounting panel by means of four screws that are screwed into the integrated threaded channels of the mounting panel. The four screws are part of the sensor.

Commercial data

Item number	1364839
Packing unit	1 pc
Minimum order quantity	3 pc
Note	Made to order (non-returnable)
Sales key	DT02
Product key	DTHABA
GTIN	4063151709358
Weight per piece (including packing)	1 kg
Weight per piece (excluding packing)	1 kg
Customs tariff number	90303320
Country of origin	DE



1364839

https://www.phoenixcontact.com/us/products/1364839

Technical data

Notes	
General	For assembly notes, see packing slip, "Downloads" tab
Product properties	
Product type	Mounting material
Dimensions External dimensions	
Width / Height / Depth	150 mm / 150 mm / 10 mm
Mounting	
Mounting type	adhesive



1364839

https://www.phoenixcontact.com/us/products/1364839

Classifications

ECLASS

ECLASS-11.0	27143192
ECLASS-13.0	27143192
ECLASS-12.0	27143192

ETIM

ETIM 8.0	EC001583	



1364839

https://www.phoenixcontact.com/us/products/1364839

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



1364839

https://www.phoenixcontact.com/us/products/1364839

Accessories

WIL-SHM-S SENSOR - Sensor

1364837

https://www.phoenixcontact.com/us/products/1364837



SNS 74-S1 sensor from Micromega Dynamics for detecting vibrations, damage, and imbalances on the rotor blade of wind turbine generators. Dual-axis accelerometer with temperature measurement. The measured values are available as 4-20~mA signals.

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com