

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		Q/T	AT		
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C (1)	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C (2)					
	VOLTAGE	100 V AC	OPERATING HUMIDITY RANGE	40 % TO 80 %					
	CURRENT	0.5 A	STORAGE HUMIDITY RANGE	40 % TO 70 % (2)					
<b>SPECIFICATIONS</b>									
ITEM	TEST METHOD			REQUIREMENTS			Q/T	AT	
CONSTRUCTION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			X	X
MARKING		CONFIRMED VISUALLY.						X	X
<b>ELECTRIC CHARACTERISTICS</b>									
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).		40 mΩ MAX.			X	-		
CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000Hz)		50 mΩ MAX.			X	-		
MILLIVOLT LEVEL METHOD									
INSULATION RESISTANCE	250 V DC		100 MΩ MIN.			X	-		
VOLTAGE PROOF	300 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.			X	-		
<b>MECHANICAL CHARACTERISTICS</b>									
MECHANICAL OPERATION	100 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: 50 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	-	
VIBRATION	FREQUENCY 10 TO 55 Hz. AMPLITUDE : 1.5 mm. 2 hrs IN 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	-	
SHOCK	490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms FOR 3 TIMES IN 3 DIRECTIONS.						X	-	
<b>ENVIRONMENTAL CHARACTERISTICS</b>									
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 hrs.			① CONTACT RESISTANCE: 50 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN.			X	-	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE: -55 → +15 ~ +35 → +85 → +15 ~ +35 °C TIME 30 → MAX 5 → 30 → MAX 5 min 5 CYCLES.			③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	-	
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 hrs.			① CONTACT RESISTANCE: 50 mΩ MAX. ② NO HEAVY CORROSION.			X	-	
HYDROGEN SULPHIDE	EXPOSED IN 3 PPM FOR 96 hrs. (TEST STANDARD: JEIDA 38)						X	-	
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING : 250 °C MAX, : 220 °C MIN, FOR 60 s 2) SOLDERING IRONS : 360 °C, FOR 5 s			NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.			X	-	
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE: 240 °C, FOR IMMERSION DURATION, 3 sec.			A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSERD.			X	-	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE					
△									
REMARK (1) TEMPERATURE RISE INCLUDED WHEN ENERGIZED. (2) THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.									
Unless otherwise specified, refer to MIL-STD-1344.									
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-071331-22					
HRS		SPECIFICATION SHEET		PART NO.		FX6A-80P-0.8SV2 (92)			
HIROSE ELECTRIC CO., LTD.		CODE NO.		CL576-0247-3-92		△ 1/1			