


NOTES: UNLESS OTHERWISE SPECIFIED


RECEPTACLE MATERIAL:
 SHELL: ZINC ALLOY, NICKEL PLATED
 INSERT AND RETAINING RING: THERMOPLASTIC
 SEAL: SILICONE RUBBER

2. BACKSHELL MATERIAL:

SHELL: ALUMINIUM ALLOY, NICKEL PLATED; LATCH SEGMENT: ALUMINIUM ALLOY, NICKEL PLATED; SCREW AND LOCK WASHER: STAINLESS STEEL; BUSHING: EPDM.

- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE: IP67 & IP69K (MATED CONDITION).
 - 3.5 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.6 RoHS COMPLIANT
- 4. APPLY TO CABLE OD SIZE: Ø11.20-Ø24.08 . CAN BE USED:
 - 4.1. WITH LARGE AND SMALL BUSHINGS IN PLACE.
- 4.2. WITH ONLY LARGE BUSHING IN PLACE.
- 4.3. WITH BOTH BUSHINGS REMOVED.
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6. SEE SPECIFIC RECEPTACLE DRAWING FOR:
 - 6.1 CONTACT SIZE AND WIRE RANGE.
 - 6.2 RETAINING RING COLOR.
- 6.3 MATING PART(S).
- 6.4 CONTACT LAYOUT AND ALL OTHER SPECIFICATIONS.





AHDM04-24-09PR-059 HD34-24-09PE-059 PART NUMBER DESCRIPTION ITEM QUANTITY MATERIALS LIST UNLESS OTHERWISE SPECIFIED SIGNATURES DATE Amphenol J. HEAD 16MAR2020 Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MJ 48036 MATERIAI SPECIFICATIONS CUSTOMER: DURAMATE AHDM RECEPT, SIZE 24, WD THD, THIS DRAWING IS SUPPLED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DA'S SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHOUS THE AMPHENOL NO PROPER TO PROPER TO PROPER THE PROPERTO OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. KIT W/ CABLE CLAMP BACKSHELL PROCESS SPECIFICATIONS B C-AHDM04-24-09PR-059 NEXT ASS'Y CALE: NONE SHEET 1 OF 1

DWG NO: AHDM04-24-09PR-059

KIT, RECPT AND BACKSHELL, SZ 24

REV: A1 SH: 1

MagnaMate™ ATHP - DuraMate™ AHDP - DuraMate™ AHDM Series - Contact Size 12 Options

Machined Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Туре		
AT60-204-12141-10	Male Contact - Pin, Nickel-plated	12	10-12	Machined		
AT62-203-12141-10	emale Contact - Socket, Nickel-plated		10-12	Machined		
AT60-220-1231	Male Contact - Pin, Gold-plated		12-14	Machined		
AT62-210-1231	emale Contact - Socket, Gold-plated		12-14	Machined		
AT60-204-12141	04-12141 Male Contact - Pin, Nickel-plated		12-14	Machined		
AT62-203-12141	Female Contact - Socket, Nickel-plated	12	12-14	Machined		

DiagnosticGrade™ Machined Contacts, Sockets & Pins • Smaller AWG for Diagnostic Applications • Gold-plated • Increased Mating Cycles • Cost-effective						
Part Number	Part Number Description Size AWG Type					
65-54749	Male Contact - DiagnosticGrade™, Pin, Gold-plated	12	20	Machined		
AT62-210-1231-1820	Female Contact - DiagnosticGrade™, Socket, Gold-plated	12	20	Machined		

	Tooling - Machined Contacts			
Part	Part Number	Description		
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)		
33	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)		

	Contact Removal Tools			
Part	Part Number	Description		
	AT11-337-1205	Contact Removal Tool, Plastic, Size 12		
	A114017	Sealing Plug, Size 12, White		

Stamped & Formed Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре	
AT60-12-0244	Male Contact - Pin, Gold-plated	12	10-12	Stamped & Formed	
AT62-12-0244	Female Contact - Socket, Gold-plated	12	10-12	Stamped & Formed	
AT60-12-0222	Male Contact - Pin, Nickel-plated	12	10-12	Stamped & Formed	
AT62-12-0222	Female Contact - Socket, Nickel-plated	12	10-12	Stamped & Formed	
AT60-12-0144	Male Contact - Pin, Gold-plated	12	12-14	Stamped & Formed	
AT62-12-0144	Female Contact - Socket, Gold-plated	12	12-14	Stamped & Formed	
AT60-12-0166	Male Contact - Pin, Nickel-plated	12	12-14	Stamped & Formed	
AT62-12-0166	Female Contact - Socket, Nickel-plated	12	12-14	Stamped & Formed	

	Tooling - Stamped & Formed Contacts						
Part	Part Number	Description					
	MFX-3973	Crimp Die - Size 12 (S&F contacts only)					
	MFX-3985	Crimp Die - Size 12 (S&F contacts only) 10-12AWG -02XX Series					
	ATT-12-00	Hand Crimp Tool - Size 12, 12AWG (S&F contacts only)					
	ATT-12-01	Hand Crimp Tool - Size 12, 10AWG (S&F contacts only)					

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 01/2022

DuraMate™ ATHD Series™ - Contact Size 8 Options

Machined Contacts, Pins and Sockets					
Part Number	Description	Size	AWG	Туре	Amps
AT60-204-08141	Male Contact - Pin, Copper Alloy, Nickel-Plated	8	8-10	Machined	60A
AT62-203-08141	Female Contact - Socket, Copper Alloy, Nickel-Plated	8	8-10	Machined	60A

	Tooling - Machined Contacts						
Part	Part Number	Description					
	WA23	Heavy Duty Pneumatic Crimp Tool -Uses Universal Positioner Part No. WA23-101DA and Crimp Locator MFX-3961					
	WA23-2	Die Assembly -for CA-5E12 Heavy Duty Pneumatic Crimp Tool, Size 8					
	WA23-10	Contact Locator, Size 8					
THE AND	96-978-22	Crimper and Dies -for Size 10mm²-185mm² Wires					

		Contact Removal Tools
Part	Part Number	Description
	AT114008	Contact Removal Tool, Plastic, Size 8, 8-10AWG

DuraMate™ ATHD Series™ - Contact Size 4 Options

Machined Contacts, Pins and Sockets					
Part Number	Description	Size	AWG	Туре	Amps
AT60-203-04141-4	Male Contact - Pin, Copper Alloy, Nickel-Plated	4	4	Machined	100A
AT60-204-0490	Male Contact - Pin, Copper Alloy, Nickel-Plated	4	6	Machined	100A
AT62-203-04141-4	Female Contact - Socket, Copper Alloy, Nickel-Plated	4	4	Machined	100A
AT62-203-04141	Female Contact - Socket, Copper Alloy, Nickel-Plated	4	6	Machined	100A

Tooling - Machined Contacts						
Part	Part Number	Description				
	WA23	Heavy Duty Pneumatic Crimp Tool -Uses Universal Positioner Part No. WA23-101DA and Crimp Locator MFX-3961				
	WA23-138DA	Die Assembly -for Heavy Duty Pneumatic Crimp Tool, Size 4				
aran i	WA23-11	Contact Locator, Size 4				
TANK ANN	96-978-22	Crimper and Dies -for Size 10mm²-185mm² Wires				

Contact Removal Tools				
Part	Part Number	Description		
	AT11-027-0405	Contact Removal Tool, Plastic, Size 4, 4AWG		