

1714791

https://www.phoenixcontact.com/us/products/1714791

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



PCB headers, nominal cross section: 2.5 mm², color: red, nominal current: 12 A, contact surface: Tin, contact connection type: Pin, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MSTBW 2,5/..-G, pitch: 5 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2,5, Pin connector pattern alignment: Standard, locking: without, mounting: without, type of packaging: packed in cardboard

Your advantages

- · Maximum flexibility when it comes to device design one header for connectors with different connection technologies
- · Well-known mounting principle allows worldwide use
- · Stand-offs enable the PCB to be cleaned or sealed

Commercial data

Item number	1714791
Packing unit	1 pc
Minimum order quantity	50 pc
Note	Made to order (non-returnable)
Sales key	AA03
Product key	AACSGL
GTIN	4055626456409
Weight per piece (including packing)	1.439 g
Weight per piece (excluding packing)	1.439 g
Customs tariff number	85366930
Country of origin	DE



https://www.phoenixcontact.com/us/products/1714791



Technical data

Product properties

Product line	COMBICON Connectors M
Product type	PCB headers
Product family	MSTBW 2,5/G
Number of positions	3
Pitch	5 mm
Number of connections	3
Number of rows	1
Number of potentials	3
Pin layout	Linear pinning
Solder pins per potential	1

Electrical properties

Nominal current I _N	12 A
Degree of pollution	3

Mounting

Mounting type	Wave soldering
Pin layout	Linear pinning

Material specifications

Material data - contact

Note	WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material	Cu alloy
Surface characteristics	Tin-plated
Metal surface contact area (top layer)	Tin (5 - 7 μm Sn)
Metal surface contact area (middle layer)	Nickel (2 - 3 μm Ni)
Metal surface soldering area (top layer)	Tin (5 - 7 μm Sn)
Metal surface soldering area (middle layer)	Nickel (2 - 3 µm Ni)

Material data - housing

Color (Housing)	red (3001)
Insulating material	PA
Insulating material group	1
CTI according to IEC 60112	600
Flammability rating according to UL 94	V0
Glow wire flammability index GWFI according to EN 60695-2-12	850
Glow wire ignition temperature GWIT according to EN 60695-2-13	775
Temperature for the ball pressure test according to EN 60695-10-2	125 °C



1714791

https://www.phoenixcontact.com/us/products/1714791

Notes

Notes on operation	In accordance with IEC 61984, COMBICON connectors have no switching power (COC). During designated use, they must not be plugged in or disconnected when carrying voltage or under load.
	7 0 0

Dimensions

Dimensional drawing	P h
Pitch	5 mm
Width [w]	15 mm
Height [h]	16.5 mm
Length [I]	12 mm
Installed height	13 mm
Solder pin length [P]	3.5 mm

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C 100 °C (dependent on the derating curve)
Ambient temperature (storage/transport)	-40 °C 70 °C
Relative humidity (storage/transport)	30 % 70 %
Ambient temperature (assembly)	-5 °C 100 °C



1714791

https://www.phoenixcontact.com/us/products/1714791

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1714791



EAC

Approval ID: B.01687



1714791

https://www.phoenixcontact.com/us/products/1714791

Classifications

UNSPSC 21.0

ECLASS

ECL	ASS-11.0	27460201
ECL	ASS-12.0	27460201
ECL	ASS-13.0	27460201
ETIM		
ETIM	18.0	EC002637
UNSPS		

39121400



https://www.phoenixcontact.com/us/products/1714791



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com