

Rubber Covered Neodymium (NdFeB) Pot Magnets -Threaded Neck

Strong Holding Force, resistant to corrosion, protects against surface damage

The arrangement of magnets and the rubber coating is ideal for use on surfaces which should not be scratched and / or where movement or slippage of a normal metal pot magnet system is a problem. This makes its use recommended for painted or varnished articles, or for applications where a strong magnetic force is needed, without marking or scratching surfaces.

The multi-pole structure of the magnets ensures a dense magnetic field on the holding surface. This allows good holding on thin surface eg. lacquered car body metal. The side displacement forces are extremely good due to the suction effect of the rubber surface.

The rubber protects the magnet in humid conditions where corrosion is likely. The holding force is not weakened even after years of use.



Threaded Neck

Product No.	Diameter mm	Height mm	Overall Height mm	Thread size mm	Holding Force kgs	Colour	Coating
E851	22	6	12.5	M4x6.5	5	Black	Santoprene Rubber
E853	43	6	21	M6x15	8.5	Black	Santoprene Rubber
E854	66	8.5	23.5	M8x15	18	Black	Santoprene Rubber
E855	88	8.5	23.5	M8x15	42	Black	Santoprene Rubber

www.eclipsemagnetics.com

Eclipse Magnetics Ltd, Atlas Way, Sheffield, S4 7QQ, England
T +44 (0)114 225 0600 F +44 (0)114 225 0525 E info@eclipsemagnetics.com

While every effort has been made to ensure the accuracy of the information in this publication please note that specifications may change without notice.



FM31278