

## Super Glue - Thin Viscosity - Penetrating 1.0oz

### Product Highlights

Thin viscosity penetrating super glue.

Use for penetrating tight fitting joints.

Bonds: Metal, Plastic, Wood, Cardboard, Paper, Ceramic, Leather and More!

### Specifications

Viscosity:	5 cP (5 mPas)
Curing Time:	3 seconds
Main Ingredient:	Cyanoacrylate
Thermal Conductivity (after curing):	0.2 W/mK
Operating Temperature (after curing):	-30°C to 90°C (-22°F to 194°F)
Size:	30ml Squeeze Bottle



### Storage and Handling

Store at 3-25°C (37-77°F). Do not freeze. Allow 4 hours for thermoset chip glue to reach an operating temperature of 20-25°C (68-77°F) before use.

### Shelf Life

>24 months (unopened)

### Transportation

This product has no shipping restrictions, when total shipment volume of Super Glue does not exceed 1000ml (qty 33 of 30ml bottles). Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.

Chip Quik Super Glue Available Part Numbers

<b>Orderable Part Number</b>	<b>Viscosity</b>	<b>Curing Time</b>	<b>Main Ingredient</b>	<b>Thermal Conductivity</b>	<b>Operating Temperature</b>	<b>Size</b>
SG1-0.5	5cP	3 seconds	Cyanocrylate	0.2 W/mK	-30°C to 90°C (-22°F to 194°F)	15 ml
SG1-1.0	5cP	3 seconds	Cyanocrylate	0.2 W/mK	-30°C to 90°C (-22°F to 194°F)	30 ml
SG2-0.5	100 cP	15 seconds	Cyanocrylate	0.2W/mK	-30°C to 90°C (-22°F to 194°F)	15 ml
SG2-1.0	100 cP	15 seconds	Cyanocrylate	0.2W/mK	-30°C to 90°C (-22°F to 194°F)	30 ml
SG3-0.5	700 cP	45 seconds	Cyanocrylate	0.2 W/mK	-30°C to 90°C (-22°F to 194°F)	15 ml
SG3-1.0	700 cP	45 seconds	Cyanocrylate	0.2 W/mK	-30°C to 90°C (-22°F to 194°F)	30 ml
SG4-1.0	700 cP	45 seconds	Cyanocrylate	0.2W/mK	-30°C to 90°C (-22°F to 194°F)	30 ml