



Banana-Banana Coil Cord allows cart users to ground carts to common grounding point on a bench.

A. Patented\* barrel type banana plug with machined contour spring support. Crimped uniformly from 4 sides for maximum strength. Fits industry standard banana jack  $\geq .157$ ". Will maintain greater than 1 pound disengagement force over the life of the cord.

B. Thermoplastic elastomer strain relief molded on. Bending Life Test average  $>1,000,000$  cycles per ANSI/ESD S20.20 (Tested per ESD S1.1). Break load average 30 pounds.

C. Wire insulation black color PVC. Break load average 30 pounds.

D. Single T-2940 tinsel conductor. Consisting of 7 strands of polyester wrapped with copper. High flex life. Equivalent is 29 gauge (cir mil and/or ohms).

| ITEM                  | Retracted Length |     | Extended Length |     |
|-----------------------|------------------|-----|-----------------|-----|
|                       | X                | Y   | Nominal         | Max |
| <a href="#">14113</a> | 24"              | 32" | 12'             | 17' |
| <a href="#">14114</a> | 30"              | 38" | 15'             | 22' |

Unless otherwise noted, tolerance is  $\pm 10\%$

\*U.S. Patent 5951337

Specifications and procedures subject to change without notice.

### Relaxed Retraction Coil Cords

# DESCO

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: [Desco.com](http://Desco.com)  
PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407  
PHONE (781) 821-8370 FAX (781) 575-0172

**DRAWING NUMBER**  
14113

**DATE:**  
September  
2011