


Data sheet

chainflex® CFROBOT4

- Measuring system cable (Class 6.1.3.3) ● For torsion applications ● PUR outer jacket
 ● Shielded ● Oil-resistant and coolant-resistant ● Flame retardant ● PVC and halogen-free
 ● Notch-resistant ● Hydrolysis and microbe-resistant



1. Outer jacket: Pressure extruded PUR mixture
2. Overall shield: Extremely torsion-resistant wrapping made of tinned copper wires
3. Banding: Plastic fleece
4. Element shield: Extremely torsion-resistant wrapping made of tinned copper wires
5. Core insulation: Mechanically high-quality TPE mixture
6. Conductor: Fine-wire strand in especially bending-stable version consisting of tinned copper wires
7. Filling: Plastic yarns



igus 36-month
chainflex cable
guarantee and
service life
calculator based
on 2 billion test
cycles per year



Example image
For detailed overview please see design table

Cable structure

Conductor	Stranded conductor in especially bending-resistant version consisting of tinned copper wires (following DIN EN 60228).
Core insulation	Mechanically high-quality TPE mixture.
Core identification	According to measuring system specification. ▶ Product range table
Element shield	Extremely torsion-resistant tinned wound copper shield.
Overall shield	Extremely torsion-resistant tinned wound copper shield. Coverage optical approx. 80 %
Outer jacket	Low-adhesion, halogen-free, highly abrasion resistant PUR mixture, adapted to suit the requirements in e-chains® (following DIN EN 50363-10-2) Colour: Steel-blue (similar to RAL 5011) Printing: white

* **Length printing:** Not calibrated. Only intended as an orientation aid.
 ① / ② Cable identification according to Part No. (see technical table).
 Example: chainflex **CFROBOT4.009 (4x(2x0.25)+(2x0.5))C**

Example image

Data sheet

chainflex® CFROBOT4

- Measuring system cable (Class 6.1.3.3) ● For torsion applications ● PUR outer jacket
 ● Shielded ● Oil-resistant and coolant-resistant ● Flame retardant ● PVC and halogen-free
 ● Notch-resistant ● Hydrolysis and microbe-resistant

Dynamic information

Bend radius	e-chain® twisted	min. 10 x d
	flexible	min. 8 x d
	fixed	min. 5 x d
Temperature	e-chain® twisted	-25 °C up to +80 °C
	flexible	-40 °C up to +80 °C (following DIN EN 60811-504)
	fixed	-50 °C up to +80 °C (following DIN EN 50305)
v max.	twisted	180 °/s
a max.	twisted	60 °/s ²
Travel distance	Robots and 3D movements, Class 1	



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



These values are based on specific applications or tests. They do not represent the limit of what is technically feasible.

Guaranteed service life according to guarantee conditions

Cycles	5 million	7.5 million	10 million
Temperature, from/to [°C]	Torsion max. [°/m]	Torsion max. [°/m]	Torsion max. [°/m]
-25/-15	±150	±90	±30
-15/+70	±180	±120	±60
+70/+80	±150	±90	±30

Minimum guaranteed service life of the cable under the specified conditions.
 The installation of the cable is recommended within the middle temperature range.

Electrical information

Nominal voltage	50 V 30 V (following UL)
Testing voltage	500 V




Example image

Data sheet

chainflex® CFROBOT4

- Measuring system cable (Class 6.1.3.3) ● For torsion applications ● PUR outer jacket
 ● Shielded ● Oil-resistant and coolant-resistant ● Flame retardant ● PVC and halogen-free
 ● Notch-resistant ● Hydrolysis and microbe-resistant

Properties and approvals

UV resistance	High
Oil resistance	Oil-resistant (following DIN EN 50363-10-2), Class 3
Flame retardant	According to IEC 60332-1-2, FT1, VW-1
Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
Halogen-free	Following DIN EN 60754
 UL verified	Certificate No. B129699: „igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year“
UL/CSA AWM	See table UL/CSA AWM for details
NFPA	Following NFPA 79-2018, chapter 12.9
EAC	Certificate No. RU C-DE.ME77.B.00295/19 (TR ZU)
REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF77. UL.05.12.D - tested by IPA according to standard DIN EN ISO 14644-1
CE	Following 2014/35/EU



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



Properties and approvals

UL/CSA AWM Details

Part No.	UL style core insulation	UL style outer jacket	UL Voltage Rating [V]	UL Temperature Rating [°C]
CFROBOT4.001	1589	20236	30	80
CFROBOT4.006	1589	20236	30	80
CFROBOT4.009	1589	20236	30	80
CFROBOT4.015	1589	20236	30	80
CFROBOT4.028	1589	20236	30	80

Example image



Data sheet

chainflex® CFROBOT4


Measuring system cable (Class 6.1.3.3) ● For torsion applications ● PUR outer jacket
 ● Shielded ● Oil-resistant and coolant-resistant ● Flame retardant ● PVC and halogen-free
 ● Notch-resistant ● Hydrolysis and microbe-resistant



Example image

Typical lab test setup for this cable series


Test bend radius R	approx. 75 - 100 mm
Test travel S/S ₂	approx. 1 - 12 m
Test duration	minimum 1.5 - 3 million double strokes
Test speed	approx. 0.5 m/s
Test acceleration	approx. 1.5 m/s ²



igus 36-month
 chainflex cable
 guarantee and
 service life
 calculator based
 on 2 billion test
 cycles per year

Typical lab test setup (torsion) for this cable series

Torsion range T	±180°/m
Length 3D e-chain®	1 m
Test duration (torsion)	minimum 3 - 5 million cycles
Test speed (torsion)	approx. 80 - 120 °/s
Test acceleration (torsion)	approx. 40°/s ²



Data sheet

chainflex® CFROBOT4

Measuring system cable (Class 6.1.3.3) ● For torsion applications ● PUR outer jacket
 ● Shielded ● Oil-resistant and coolant-resistant ● Flame retardant ● PVC and halogen-free
 ● Notch-resistant ● Hydrolysis and microbe-resistant

Typical application areas

- For heaviest duty applications with torsion movements, Class 6
- Especially for robots and 3D movements, Class 1
- Almost unlimited resistance to oil, Class 3
- Torsion $\pm 180^\circ$, with 1m cable length, Class 3
- Indoor and outdoor applications, UV-resistant
- Robots, Handling, spindle drives

igus 36-month
chainflex cable
guarantee and
service life
calculator based
on 2 billion test
cycles per year

Technical tables:

Mechanical information

Part No.	Number of cores and conductor nominal cross section [mm ²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CFROBOT4.001	(3x(2x0.14)C + (4x0.14)+(2x0.5)C)	10.5	62	115
CFROBOT4.006	(3x(2x0.14)C+(4x0.14)+(4x0.22)+(2x0.5)C)	11.5	74	135
CFROBOT4.009	(4x(2x0.25)+(2x0.5)C)	9.0	48	90
CFROBOT4.015	(4x(2x0.14)+4x0.5)C	9.0	49	91
CFROBOT4.028 ¹³⁾	(2x(2x0.20)+(2x0.38)C)	7.5	44	72

¹³⁾ Colour outer jacket: Yellow-green (RAL 6018)

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
 G = with green-yellow earth core x = without earth core

Technical tables:

Electrical information

Conductor nominal cross section [mm ²]	Maximum conductor resistance at 20 °C (following DIN EN 50289-1-2) [Ω /km]	Maximum current rating at 30 °C [A]
0.14	146.0	2.5
0.2	94.0	3.5
0.22	91.0	4
0.25	86.0	5
0.38	55.0	7
0.5	43.0	10

The final maximum current rating depends among other things on the ambient conditions, the type of the installation and the number of loaded cores.

Example image

igus® chainflex® CFROBOT 4

Data sheet


chainflex® CFROBOT4

- Measuring system cable (Class 6.1.3.3) ● For torsion applications ● PUR outer jacket
 ● Shielded ● Oil-resistant and coolant-resistant ● Flame retardant ● PVC and halogen-free
 ● Notch-resistant ● Hydrolysis and microbe-resistant



Design table

Part No.	Core group	Colour code	Core design
CFROBOT4.001	3x(2x0.14)C	green/yellow, black/brown, red/orange	
	4x0.14	grey/blue/white-yellow/white-black	
	2x0.5	brown-red/brown-blue	
CFROBOT4.006	3x(2x0.14)C	green/yellow, black/brown, red/orange	
	(4x0.14)	grey/blue/white-yellow/white-black	
	(4x0.22)	yellow-brown/grey-brown/green-black/green-red	
	(2x0.5)	brown-red/brown-blue	
CFROBOT4.009	4x(2x0.25)	brown/green, blue/violet, grey/pink, red/black	
	2x0.5	white, brown	
CFROBOT4.015	4x(2x0.14)	brown/green, yellow/violet, grey/pink, red/black	
	4x0.5	blue, white, brown-green, white-green	
CFROBOT4.028	2x(2x0.20)	green/yellow, pink/blue	
	(2x0.38)	red/black	



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year



Example image