

28156.6 PVC-PTSA 50X30 K GR

Device and installation marker, Length: 30 mm, Width: 50 mm, Colour: grey

RAL: Ähnlich 7035

Business data

Article number	<u>28156.6</u>
Article name	PVC-PTSA 50X30 K GR
GTIN (EAN)	4044211213084
Packaging unit	150
Quantity unit	PC
Number of markers per card	6 ST
Weight per piece (not including packaging)	2.52 g
Weight per piece (including packaging)	2.52 g
Unit of weight	G
Customs number	39199080
Country of origin	IT
Prio-Article	28156.7
Product description	Device and installation marker

28156.6 PVC-PTSA 50X30 K GR

Technical data

Dimensions

Length	30 mm
Width	50 mm
Hole diameter	22.5 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Mounting	Self-adhesive
Software code	1001

Environmental Product Compliance

REACH Conform	Yes
REACH Candidate Substance Note	No
RoHS Conform	Yes

Media

28156.6 PVC-PTSA 50X30 K GR

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST