



Main

| | |
|---------------------------|--|
| Range of Product | Harmony XVR |
| Product or Component Type | Prewired rotating mirror beacon |
| Sound signalling | Without |
| Device short name | XVR |
| Mounting diameter | 4.17 in (106 mm) |
| IP degree of protection | IP55 IEC 60529 with accessory) IP23 IEC 60529 |
| [Us] rated supply voltage | 24 V AC/DC |
| Light source | High luminosity LED, blue |

Complementary

| | |
|--|---|
| Material | ABS (acrylonitrile butadiene-styrene) body part PMMA (polymethyl methacrylate) globe |
| CAD overall width | 4.17 in (106 mm) |
| CAD overall depth | 4.17 in (106 mm) |
| Net Weight | 1.10 lb(US) (0.5 kg) |
| Marking | CE |
| Product mounting | By 3 M4 screws |
| Supply voltage limits | 19...30 V DC 21.6...26.4 V AC |
| [Uimp] rated impulse withstand voltage | 0.8 kV |
| Current Consumption | 125 mA |
| Flashing frequency | 2.3 Hz |
| Clamping connection capacity | 0.83 mm ² |
| AWG gauge | AWG 18 |
| Cable length | 15.75 in (400 mm) |

Environment

| | |
|---------------------------------------|------------------------------|
| Standards | EN 61000-6-2 EN 61000-6-4 |
| Product Certifications | UL |
| Protective treatment | TC |
| Ambient Air Temperature for Storage | -31...158 °F (-35...70 °C) |
| Ambient air temperature for operation | 14...122 °F (-10...50 °C) |
| Electrical shock protection class | Class II IEC 61140 |

Ordering and shipping details

| | |
|-----------------------|--------------------------|
| Category | 22617 - XVC TOWER LIGHTS |
| Discount Schedule | XV |
| GTIN | 3606480033100 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 22.01 oz (624 g) |
| Returnability | No |
| Country of origin | ID |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 5.31 in (13.5 cm) |
| Package 1 width | 5.51 in (14 cm) |
| Package 1 Length | 7.68 in (19.5 cm) |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 8 |
| Package 2 Weight | 13.77 lb(US) (6.244 kg) |
| Package 2 Height | 11.81 in (30 cm) |
| Package 2 width | 15.75 in (40 cm) |
| Package 2 Length | 23.62 in (60 cm) |
| Unit Type of Package 3 | PAL |
| Number of Units in Package 3 | 32 |
| Package 3 Weight | 44.02 lb(US) (19.968 kg) |
| Package 3 Height | 23.62 in (60 cm) |
| Package 3 width | 31.50 in (80 cm) |
| Package 3 Length | 12.60 in (32 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Rotating Mirror Beacon

Dimensions

mm
in.



