



Technical specification :

Rated voltage: IEC 61076-2-104	60 V
Current rating: IEC 61076-2-104	3 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	>=100

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Coupling screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

Installation specification:

Recommended torque:	0,4 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 9: 36-000210

Contact assignment:

- 1 brown
- 3 blue
- 4 black

Part no:	Description:	Length L:	Cable:
42-10076	SAL - 8 - RSU3 - 2 / K1	2m	TPU, UL 20549, black, 3x0,25mm ² Cable: 781-K12300
42-10077	SAL - 8 - RSU3 - 3 / K1	3m	
42-10078	SAL - 8 - RSU3 - 5 / K1	5m	
42-10079	SAL - 8 - RSU3 - 10 / K1	10m	
42-xxxxx	SAL - 8 - RSU3 - ... / K1	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND
Directive 2002/95/EC RoHS compliant

Index: a 17.03.2011 VF Ä3945
Coupling screw modified, spanner flats added, data sheet modified

tolerance of cable: L < 4m: L + 40mm
L > 4m: L + 1%

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH

dim. in mm		
	date	name
drawn	05.10.07	Franz
appd.	05.10.07	Mankopf



title:
Male connector M8x1 axial screw/ snap

dwg no:
42K1A019

part no:
see table