

## Cable gland - G-INB-M20-S68N-PEPDS-LG - 1415174

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Polyamide, Application: Standard, External cable diameter 6 mm ... 13 mm, Shielding: No, Connecting thread: M20

The figure shows version G-INB-M25-M68N-PEPDS-LG



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 10 pc    |
| Weight per Piece (excluding packing) | 22.0 g   |
| Custom tariff number                 | 39269097 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|                                  |                |
|----------------------------------|----------------|
| Length                           | 103 mm         |
| Length without connecting thread | 91 mm          |
| Connecting thread diameter       | 20 mm          |
| Wrench size, union nut           | 24 mm          |
| Wrench size, support             | 24 mm          |
| Hexagon angular dimension GRP    | 27 mm          |
| Length of the connecting thread  | 12 mm          |
| External cable diameter          | 6 mm ... 13 mm |

#### Ambient conditions

|                                 |                            |
|---------------------------------|----------------------------|
| Degree of protection            | IP68 (5 bar / 0.5 h)       |
|                                 | IP69K                      |
| Ambient temperature (operation) | -40 °C ... 100 °C (static) |

#### General

# Cable gland - G-INB-M20-S68N-PEPDS-LG - 1415174

## Technical data

### General

|                                |                     |
|--------------------------------|---------------------|
| Cable gland material           | Polyamide           |
| Seal material                  | EPDM                |
| Shielded                       | No                  |
| Thread type on connection side | M20                 |
| Color                          | light grey RAL 7035 |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27149109 |
| eCl@ss 6.0 | 27149109 |

### ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC000441 |
|----------|----------|

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / GOST-R / cULus Recognized

---


#### Ex Approvals

---

#### Approvals submitted

---

### Approval details


|   |
|---|
| UL Recognized  |
|---|

|  |
|--|
| cUL Recognized  |
|--|

# Cable gland - G-INB-M20-S68N-PEPDS-LG - 1415174

## Approvals

GOST-R 

cULus Recognized 

## Drawings

Dimensional drawing

