


ASI1492J3



ASI1492J4

SPECIFICATIONS				
Wire Range	28-12 AWG		28-10 AWG	
Current Rating	25		35	
Voltage Rating	600		600	
Dimensions (L x H x W)	60 x 39.5 x 5 mm		60 x 39.5 x 6 mm	
<b>Ordering Information</b>	<b>Order#</b>	<b>Pcs./Pkg.</b>	<b>Order#</b>	<b>Pcs./Pkg.</b>
Terminal Block	ASI1492J3	50	ASI1492J4	50
<b>Accessories</b>				
End cover	ASI1492EBJ3	25	ASI1492EBJ3	25
<b>Circuit Bridges</b>				
Push-in 10 position	ASIUFBS105	10	ASIUFBS106	10
TB Markers Blank	ASKB512B 10 Strips of 10 Markers		ASIKB612B 10 Strips of 10 Markers	
<b>End-Stop (snap-on)</b>				
Black	ASIUD1B	25	ASIUD1B	25
<b>DIN Rail (2 meters)</b>				
7.5 x 35 mm Slotted	PR005	1	PR005	1
7.5 x 35 mm Non-Slotted	PR003	1	PR003	1
15 x 35 mm Slotted	PR006	1	PR006	1
15 x 35 mm Non-Slotted	PR007	1	PR007	1

The ASI1492 series of IEC terminal blocks is the first terminal block series that is totally compatible with manufacturers such as Allen-Bradley®. The ASI1492 terminal blocks feature the same quality design features and materials of the popular 1492 series with added improvements including nickel plated copper alloy metal bodies and plated high tensile alloy crews. Careful attention to detail has been given to this product family so that accessories are interchangeable and the costs associated with using another brand are eliminated..

One of the added features with the ASI1492 series terminal blocks along with others of similar spacing, is the ability to use a low-cost plug-in jumper.

The ASI1492 series meets international approvals including UL and cUL and all products are RoHs compliant.

A short cross-reference is shown below while a more complete one that can be found at [www.asi-ez.com](http://www.asi-ez.com) or by calling ASI toll free at **877-650-5160**.

ASI Type	Allen-Bradley
ASI1492J3	1492-J3
ASI1492J4	1492-J4