




Units:mm



- Electrical test:
1. 100% short, open, miswire test
  2. Conduct resistance: 5 Ohm(max)
  3. Insulation resistance: 10Mohm(min)
  4. dielectric test: DC 300V

⑧	TIE	2	BLACK L=80mm
⑦	PE BAG	1/10	CLEAR SIZE: 280*330*0.05mm PRINT BLACK"MADE IN CHINA"+"10PCS"
⑥	PE BAG	1	CLEAR SIZE: 130*230*0.05mm PRINT BLACK"MADE IN CHINA"+"1PC"
⑤	S/R	3.0g	BLACK PVC 40P (Mould NO.:SR-048)
④	IN JACKET	1.6g	CLEAR LD-PE (Mould NO.:NM-006)
③	OUT JACKET	6.6g	PVC-40P RED(RD-35),(Mould NO.:WM-009)
②	IN JACKET	1.6g	CLEAR LD-PE (Mould NO.:NM-006)
①	CABLE CONN	4	NOUL 28#(10/0.10+28/0.10)*2F JACKET BLACK OD2.8*5.6mm
NO.	NAME	QTY	RCA PLUG MALE 梅花型 TYPE NI-PLATED INSULATOR COLOR:BROWN

NOTE:  
1.小PE袋大PE袋对应料号,包袋数量及时向印刷样式:  
AGSUN Electronics, Inc.  
770-20011-00150  
10PCS. → ROHS 525 表示52.0099克/每袋产品生产用标识  
印字人产编号  
印刷时的袋数数量

2.外箱两个侧袋ITEM NO后面各贴一个35\*22mm ROHS标签。

# CnC Tech, LLC

Industrial Cable and Connector Technology

DRAWN BY	LICHENG	DRAWING NO.	VG/LJQ-094-082-B
CHECKED BY		CUSTOMER	CnC
APPROVAL BY		ITEM NO.	770-20011-00150
DECIDE BY		DATE	2012-12-28
VERSIONS/EDITEON	A/0	PROJECTION	