

## Specification Sheet

Part Number: 181-00665



Narrow fingers reduce fanning of wires to terminal blocks, providing a neater appearance.

Each finger features a double restriction to hold wires in the bottom portion of the duct, simplifying installation.

Mounting holes are uniform in size to those in slotted and solid wall duct but are provided every two inches to accommodate compact designs and provide ease of installation.

Nonpermanent adhesive allows repositioning prior to final installation.

High Density Slotted Wall Wiring Duct, 4" x 2", Adhesive, PVC, White, 120ft/Carton

Article Number 181-00665

Type SLHDA4X2

Color White (WH)

Quantity Per carton

Product Description HellermannTyton High-Density Slotted Wall Wiring Duct features narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 4" x 2", Adhesive, PVC, White, 120ft/Carton

|                                  |                         |
|----------------------------------|-------------------------|
| Global Part Name                 | SLHDA4X2-PVC-WH         |
| Length L (Imperial)              | 6.0                     |
| Length L (Metric)                | 1.83                    |
| Fixation Method                  | Adhesive                |
| Width W (Imperial)               | 4.0                     |
| Width W (Metric)                 | 101.6                   |
| Height H (Imperial)              | 2.07                    |
| Height H (Metric)                | 52.6                    |
| Mounting Hole Centers (Imperial) | 2.0                     |
| Material                         | Polyvinylchloride (PVC) |
| Material Shortcut                | PVC                     |
| Halogen Free                     | No                      |
| UV Resistant (Yes/No)            | No                      |
| Operating Temperature            | +122°F (+50°C)          |
| Reach Compliant (Article 33)     | No                      |

|                             |  |
|-----------------------------|--|
| ROHS Compliant              | Yes  |
| Certification/Specification | CSA UL EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A |
| UL Recognized (US)          | Yes  |
| Package Quantity (Imperial) | 120.0  |
| Package Quantity (Metric)   | 36.58  |
| Customs Number              | 3925900000                                       |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)