



LOCK WASHER HEX NUT SPRING WASHER RED HAT

Note: parts in bulk,  
100SET/bag

ELECTRICAR CHARACTERISTICS REQUIREMENTS:

- 1.Product must be 100% conduction,open circuit short circuit test.
- 2.Conductive resistance : 20Ω
- 3.Rated voltage: AC 60V
- 4.Withstand voltage: AC 200V
- 5.Insulation resistance:500m Ω
- 6.characteristic impedance : 50Ω
- 7.Adopt environmental protection process and meet ROHS requirements
8. Tensile test: 1.5kg~
9. The general tolerance shall prevail if no tolerance is noted

RoHS Compliant

5	COVER	-	RED HAT PACKING SMA	1	-
4	HEAT SHRINK SLEEVE	-	2.0*18MM BLACK HEAT SHEINK SLEEVE	1	-
3	SMA FEMALE	-	11*1.78-ZYK-Back plug riveting and gold plating	1	-
2	IPEX-1.78 CONN	-	IPEX-1.78 BRASS GOLD	1	-
1	COAXIAL CABLE	-	RG1.78 BROWN-48-Double silver-PTFE	1	55
ITEM	PART No.	VENDOR	DESCRIPTION	Q'TY	OVERALL WIRE LENGTH

MATERIAL SPECIFICATION

△3				DRAWN BY	CHECKED BY	APPROVED BY	CONFIRMED BY	DESCRIPTION	 瀚荃股份有限公司 CviLux Corporation	CUST. CODE
△2				LuLu	Iron	Iron	Waleed	RF CABLE		CUC
△1				08/21.20'	08/21.20'	08/21.20'	08/21.20'	SHEET: 1 OF 1	DRAWING No. DH50629A	CUSTOMER P/N
SYM	NAME	DATE	REVISIONS						CviLux P/N DH-20G50015	-