

# ATGBICS AFBR-89CDDZ-AB1 Avago Broadcom Compatible Transceiver QSFP28 100GBase-SR4 (850nm, MMF, 100m, MPO, DOM)

**Brand :** ATGBICS

**Product code:** AFBR-89CDDZ-AB1-C



**Product name :** AFBR-89CDDZ-AB1 Avago Broadcom Compatible Transceiver QSFP28 100GBase-SR4 (850nm, MMF, 100m, MPO, DOM)

AFBR-89CDDZ-AB1 Avago Broadcom Compatible Transceiver QSFP28 100GBase-SR4 (850nm, MMF, 100m, MPO, DOM)

ATGBICS AFBR-89CDDZ-AB1 Avago Broadcom Compatible Transceiver QSFP28 100GBase-SR4 (850nm, MMF, 100m, MPO, DOM):



ATGBICS AFBR-89CDDZ-AB1 100GBase-SR4 QSFP28 supports a distance of up to 100m over OM4 multi-mode fibre (MMF) using a wavelength of 850nm via an MPO connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of AFBR-89CDDZ-AB1= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

Performance		Power	
SFP transceiver type *	Fiber optic	Input voltage	3.3 V
Maximum data transfer rate *	100000 Mbit/s	Maximum voltage	3.5 V
Interface type *	QSFP28	Power consumption (typical)	4 W
Single-mode fiber (SMF) supported	✗	Operational conditions	
Multi-mode fiber (MMF) supported	✓	Maximum operating temperature	70 °C
Fiber optic connector	MPO	Operating temperature (T-T)	0 - 70 °C
SFP transceiver standard	SR4	Storage temperature (T-T)	-40 - 85 °C
Maximum transfer distance	100 m	Operating relative humidity (H-H)	0 - 95%
Wavelength	850 nm	Storage relative humidity (H-H)	0 - 95%
Ethernet LAN	✓	Weight & dimensions	
Ethernet interface type	100 Gigabit Ethernet	Width	13.5 mm
Digital Diagnostics Monitoring (DDM)	✓	Depth	72.4 mm
		Height	18.4 mm
		Weight	42 g
Features		Packaging data	
Product colour	Silver	Number of products included	1 pc(s)
Housing material	Metal	Package type	Box
Plug and Play	✓	Technical details	
Hot-Plug support	✓	Sustainability compliance	✓
Hot-swap	✓	Sustainability certificates	RoHS
Easy to install	✓	Doesn't contain	Lead
Country of origin	China		
Brand compatibility	Avago Technologies		
Certification	CE, FCC, RoHS		



5056468770271

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2023. Prints or copies of Information are only valid on the printed Publication date