



LEAD FREE PART NUMBER

SHELL	A±0.38	B±0.12	C±0.10	D±0.25	E±0.07	PART NUMBER	PART NUMBER
09	30.81	24.99	18.00	16.21	10.96	D09S81C4G*00LF	D09S81C6G*00LF
15	39.14	33.32	26.32	24.54	19.18	D15S81C4G*00LF	D15S81C6G*00LF
25	53.03	47.04	40.04	38.25	33.12	D25S81C4G*00LF	D25S81C6G*00LF
37	69.32	63.50	56.50	54.71	49.68	D37S81C4G*00LF	D37S81C6G*00LF
						Gold flash	0.76 µ gold/GxT

Threaded ØT M3 = I
Threaded ØT 4.40 = V

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:
SEE DRAWING C01-8646-0001

mat'l. code				surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection		product family	
-								MM		D-SUB	
ltr ecn no dr date				tolerances unless otherwise specified						title	
J	ELX-I-18050	MP	2014/06/23	.0±0.3						FEMALE CONNECTOR DELTA-D EUROPE	
K	ELX-I-33101	GM	2019-04-01	.00±0.1						RIGHT ANGLED PRESS FIT	
L	ELX-I-34612	GM	2019-20-08	.000±0.05						dwg no sheet 1 of 1 size	
				angles linear		scale 2:1				C01-8646-0544 A3	
				0°±2'						type Product Customer Drawing	
dr				PESSON		1997/10/15					
enr				GREGAR M		2019-04-01					
chr				MITHUN PAUL		2019-20-08					
appd				SANJOJ P K		2019-20-08					
sheet index		revision sheet		L							
		1									